

Данни за артикула: BK090206--

Wall-mounting Distribution Board 3-row 54MW transparent IP65

UV stability and weather resistant, 1000VDC; Plastic material ABS, 3x18MW, H=638
W=432 D=160, 2x N+PE (22x16mm²)



SCHRACK-Info

- Wall-mounted enclosures with one transparent door inclusive UV-Protection
- Lock: Pressure-operated mechanism, a small cylinder can be installed
- Cable Entry by elastic rubber membranes
- Includes PE and N terminals
- Halogen-free plastic materials
- Protection class II
- UV stability and weather resistant

- Rated voltage 400VAC, 1000VDC
- Ambient temperature: -25° to +85°C
- Material: ABS
- Degree of protection IP65
- Resistance to impact: IK07
- RAL7035 light grey

Технически данни

Нето ширина (mm)	432,00
Нето височина (mm)	638,00
Дълбочина (mm)	160,00
Нето тегло (kg)	5,72
EAN	9004840817959
Разсейвана мощност (W)	-35,00
Мин. околна температура (°C)	-25
Макс. околна температура (°C)	85

Таблица с артикули

Описание	Артикулен No.
Wall-mounting Distribution Board 3-row 54MW transparent IP65 UV stability and weather resistant, 1000VDC; Plastic material ABS, 3x18MW, H=638 W=432 D=160, 2x N+PE (22x16mm²)	BK090206
Акcesoари	
Секретна ключалка за BK09, IP65	BK090097