


Данни за артикула: BKUP401GA-

UP-Wohnungsverteiler 3-reihig mit FI "G", Typ "A"

Bestückt und verdrahtet - IP40, Schutzklasse II, 36+6 TE, Vorsicherung max. 25A, LS-FI-Schalter Kennl.B, 16A, FI-GA, C16/3+N, 4xB13 1+N, 2xB16 1+N, RAL9003 Signalweiß, Breite=346mm, Höhe=592mm, Tiefe=96mm



Технически данни

Нето ширина (mm)	346,00
Нето височина (mm)	592,00
Дълбочина (mm)	96,00
Нето тегло (kg)	5,90
EAN	9004840870862
Разсейвана мощност (W)	-80,50
Версия	Flush-mounted partition wall with door
Материал на вратата	ламарина
Брой модули на ред	12+2
Степен на защита - IP	IP40
Цвят	RAL 9003 (Signalweiß)
ШхВхД mm	346x592x96

Таблица с артикули

Описание	Артикулен No.
UP-Wohnungsverteiler 3-reihig mit FI "G", Typ "A" Bestückt und verdrahtet - IP40, Schutzklasse II, 36+6 TE, Vorsicherung max. 25A, LS-FI-Schalter Kennl.B, 16A, FI-GA, C16/3+N, 4xB13 1+N, 2xB16 1+N, RAL9003 Signalweiß, Breite=346mm, Höhe=592mm, Tiefe=96mm	BKUP401GA