

Данни за артикула: DS428020-B

Комуникационен шкаф стоящ DS, W800xH1970xD1200, 19", 42U

RAL9005 Black



SCHRACK-Info

TECHNICAL DATA

- The frame, the door, the side panels, the roof plate and the base plate are made of 1.0 mm sheet metal. The mounting for the optional castors is made of 2.0 mm sheet metal. All these parts are made of DC01 quality sheet steel. The vertical rails are made of galvanised sheet metal with a thickness of 2.0mm.
- Welded powder-coated sheet steel skeleton
- Height: 42U
- Width: 800mm
- Depth: 1200mm
- Colour:
 - Black RAL9005.
- Maximum Load:
 - 15-22U: 300kg
 - 27-47U: 400kg
- Degree of protection: IP20
- 4 mm thick safety glass doors with handsome swing handle. Prepared for half-cylinder type locks. Halfcylinder lock (Order-number: DV900333), Depth= 40mm, Diameter= 17mm, Fixing= M5 Screw, optional available.
- Doors hinged right. Can be changed to hinging on left.
- External hinge system allows up to 180 degree door opening angle.
- Glass doors can be replaced by optional DSRT doors (full metal or perforated, full width or double-wing).

- Removeable and lockable side-panels. Key included. For better passive cooling, side-panels can be replaced by optional perforated side-panels DSRS.
- Removeable and lockable rear-panel. Key included. Rear panel can be replaced by optional DSRT doors (glass, full or perforated metal, full width or double-wing) or by perforated rear-panel DSRR.
- 19" rails (4 pcs.) galvanised, continuously depthadjustable. Numbering of Height-Units (U) by laser for easy readability.
- In 800mm wide DS enclosures, you can choose to adjust the 19" rails to a width of 21".
- In 900, 1.000 and 1.200 mm deep DS enclosures, there is an additional pair of vertical rails installed in half depth. This makes installation of high depth accessories together with standard accessories possible at the same time.
- Space between front vertical 19"-rail and door glass at max. spacing:
 - W600 – 35mm
 - W800 – 50mm
- Space between rear vertical 19"-rail and rear panel at max. spacing:
 - W600 – 35mm
 - W800 – 55mm
- Maximum distance between vertical rails (19"-rails) in free-standing cabinets:
 - W600 x D400 – 310mm
 - W600 x D600 – 510mm
 - W600 x D800 – 710mm
 - W600 x D900 – 810mm
 - W600 x D1000 – 910mm
 - W600 x D1200 – 1110mm
 - W800 x D600 – 470mm
 - W800 x D800 – 670mm
 - W800 x D900 – 770mm
 - W800 x D1000 – 870mm
 - W800 x D1200 – 1070mm
- Maximum usable depth in free-standing cabinets when installed e.g. on shelves:
 - D400 – 375mm
 - D600 – 575mm
 - D800 – 775mm
 - D900 – 875mm
 - D1000 – 975mm
 - D1200 – 1175mm
- Spacing between vertical 19"-rails: 451 mm
- Roof construction with opening, 19" punched. Flexible covered by removable plates of different heights to allow installation of fan-units and cable-entry panels. Remaining opening can be closed by use of one these plates.
 - D400 - Opening: 6U, Covering: 1 x 4U and 1 x 2U
 - D600 - Opening: 8U, Covering: 1 x 4U and 2 x 2U
 - D800 - Opening: 10U, Covering: 2 x 4U and 1 x 2U
 - D900 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
 - D1000 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
 - D1200 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
- Floor construction with opening, 19" punched. Covered by removable plate in full height.
 - D400 - Opening: 6U, Covering: 1 x 6U
 - D600 - Opening: 8U, Covering: 1 x 8U
 - D800 - Opening: 10U, Covering: 1 x 10U
 - D900 - Opening: 12U, Covering: 1 x 12U

- D1000 - Opening: 12U, Covering: 1 x 12U
- D1200 - Opening: 12U, Covering: 1 x 12U
- Roof unit assemblies can also be fitted to floor section. Optional base required.
- Cable entry possible via roof, floor and rear panel. Delivered with demountable or break-out blanking plates.
- Brush strip panel for roof (DBK24800) optional.
- Air vents for passive ventilation.
- Earthing:
 - M8-Earthing point plus 19"-Earthingset in the rear of the cabinet
 - FastOn-Earthing-connections to all dismountable parts pre-installed
- Included assembly materials:
 - 16 x Cage nuts, bolts and washers M6
 - 4 x Levelling feet
- Wide range of available accessories (bases, fan-units, cable entry panels, fixed shelves, patch panels, cable management, PDUs, doors, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

Технически данни

Нето ширина (mm)	800,00
Нето височина (mm)	1.970,00
Дълбочина (mm)	1.200,00
Нето тегло (kg)	122,00
Мин. околна температура (°C)	0
Макс. околна температура (°C)	40
Приложимо за HU	42U-1970mm
Цвят	RAL 9005 (black)

Таблица с артикули

Описание	Артикулен No.
Комуникационен шкаф стоящ DS, W800xH1970xD1200, 19",42U RAL9005 Black	DS428020-B
Акcesoари	
Страничен панел за цокъл, D=1200, H=120 за шкаф DS123415689 RAL9005 Black	DSOT1220-B
Base front-/rear-cover, W=800 f.DS/DSZ/DSS-enclosures RAL9005 RAL9005 Black	DSOF1280-B
Half cylinder lock keyed EK 333 including 1 key including 1x countersunk screw M5x16mm V2A	DV900333S
Четка за кабелен вход, 2U, RAL9005	DBK24800-B

Таблица с артикули

Описание	Артикулен No.
Акcesoари	
Таванен вент. модул с 2 вент. и термостат, 19", 4U, RAL9005 Black for freestanding enclosures DS/DSZ and DSS	DLT44802-B
19" Аранжиращ панел, 5 метални пръстена 80x40mm, 1U, RAL9005	DBC14805-B
19" Аранжиращ панел, 5 пръстена 40x83mm, 1U, RAL9005 Черно	DBK14805-B
19" Фиксирана тава, до 80kg Товар, D=450mm, 1U, RAL9005	DFS14845-T
19" Алюминиев профил PDU, 9xшuko, 1U, 3m-кабел, RAL7035	IU070114-3
Разклонител за 19", 7 x Шuko с арестор, 1.25U, RAL7035 2m-connector cable, RAL7035	IU070113
19" Разклонител, 9xШuko, с ключ, 1U, 2m кабел, черно, ALU ALU Профил	Q7070114-A
19" Разклонител, 7xШuko, с ключ, 1U, защита от пренапрежение 2m-кабел, черен, ALU	Q7070113-A
IT METER LINE PDU пасивен, Вх: CEE 16A черв., Изх: 12xC 13,6xШuko	HSMPP312
PDU-държач вертикален за 800 mm широки DS и DSZ-кутии, 1U 1 PU = 2 pcs., Installation on vertical rail, Assembly material included	DSPDU010
19" Монтажен комплект M6, 50 броя: винт, гайка, шайба	DSSRA050
19" mounting plate, 14U, sheet steel, perforated including screws and cage nuts	DMP1914
Осветителен модул LED, магнит, 230VAC, със сензор за врата автоматична функция, при отваряне на вратата, външен PSU	DTLIGHT01
Switch 24xRJ45 10/100/1000, Silent, w/o fan, internal PSU Metal-Chassis, 19"	QLGSW2457
Пач панел 19" празен, 24 модула (SFA)(SFB), 1U, черен ECO черно, единично закрепване, фиксиране на пач кабелите	HSERO240SP