


Данни за артикула: DSZ426020-

Комуникационен шкаф разглобяем DSZ W600xH1970xD1200, 19" 42U



SCHRACK-Info

- Powder-coated sheet steel skeleton 1,5mm
- Height: 42U
- Width: 600mm
- Depth: 1.200mm
- Demountable Parts:
 - Front Part: 105mm
 - Rear Part: 105 mm
- Main Part welded:
 - 390mm at 600 deep enclosure
 - 590mm at 800 deep enclosure
 - 690mm at 900 deep enclosure
 - 790mm at 1.000 deep enclosure
 - 990mm at 1.200 deep enclosure
- Colour: Light Grey RAL 7035,
- Frame Blue RAL 5005
- Maximum load:
 - 15 – 22U: 300 kg
 - 27 – 47 U: 400kg
- Degree of protection: IP20

- 4 mm thick safety glass doors with handsome swing handle. Prepared for half-cylinder type locks. Halfcylinder lock (Order-number: DV900333), Depth= 40mm, Diameter= 17mm, Fixing= M5 Screw, optional available.
- Doors hinged right. Can be changed to hinging on left .
- External hinge system allows up to 180 degree door opening angle.
- Front glass door can be replaced by optional DSRT metal door (full metal or perforated).
- Removeable and lockable rear and side panels. Key included.
- Rear panel can be replaced by optional DSRT rear door. Glass- or metal door (full metal or perforated). 19" rails (4 pcs.) galvanised, continuously depthadjustable. Numbering of Height-Units (U) by laser for easy readability.
- In 800mm wide DSZ enclosures, you can choose to adjust the 19" rails to a width of 21" .
- In 900, 1.000 and 1.200 mm deep DSZ enclosures there is an additional pair of vertical rails installed in half depth. This makes installation of high depth accessories together with standard accessories at the same time possible.
- Space between front vertical 19"-rail and door glass at max. spacing:
 - W600 – 43mm
 - W800 – 50mm
- Space between rear vertical 19"-rail and rear panel at max. spacing:
 - W600 – 45mm
 - W800 – 55mm
- Maximum distance between vertical rails (19"-rails) in free-standing cabinets:
 - W600 x D600 – 494mm
 - W600 x D800 – 694mm
 - W600 x D900 – 794mm
 - W600 x D1000 – 894mm
 - W600 x D1200 – 1.094mm
 - W800 x D600 – 470mm
 - W800 x D800 – 670mm
 - W800 x D900 – 770mm
 - W800 x D1000 – 870mm
 - W800 x D1200 – 1.070mm
- Maximum usable depth in free-standing cabinets when installed e.g. on shelves:
 - D600 – 575mm
 - D800 – 775mm
 - D900 – 875mm
 - D1000 – 975mm
 - D1200 – 1.175mm
- Spacing between vertical 19"-rails: 451 mm
- Roof construction with 19" punching.
- 600 mm deep DSZ enclosures come with 8U deep roof aperture, flexible covering with 1 x 4U and 2 x 2U cover plates.
- 800 mm deep DSZ enclosures come with 10U deep roof aperture, flexible covering with 2 x 4U and 1 x 2U cover plates.
- 1.000 and 1.200 mm deep DS enclosures come with 12U deep roof aperture, flexible covering with 2 x 4U and 2 x 2U cover plates.
- Floor construction with 19" punching.
- Roof unit assemblies can also be fitted to floor section. Optional base required.
- Cable entry possibility via roof, floor and rear panel. Delivered with blanking plates.
- Brush strip cable entry panel for roof (DBK24800) optional available.
- Air vents for passive ventilation Fully pre-wired earthing.
- Includes M8 earthing point and earthing kit. Including assembly materials: 24 x Cage nuts, bolts and washers M6, 4 x Levelling feet.

- Wide range of available accessories (bases, fan-units, cable entry panels, fixed shelves, patch panels, cable management, PDUs, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

Технически данни

Нето широчина (mm)	600,00
Нето височина (mm)	1.970,00
Дълбочина (mm)	1.200,00
Нето тегло (kg)	110,80
Мин. околна температура (°C)	0
Макс. околна температура (°C)	40
Приложимо за HU	42U-1970mm
Цвят	RAL 7035 / RAL 5005 (light grey / blue)

Таблица с артикули

Описание	Артикулен No.
Коммуникационен шкаф разглобяем DSZ W600xH1970xD1200, 19" 42U	DSZ426020
Акcesoари	
Half cylinder lock keyed EK 333 including 1 key including 1x countersunk screw M5x16mm V2A	DV900333S
Таванен панел с вход за кабели, с четка, 2U, RAL7035	DBK24800
Таванен вент. модул с 2 вент. и термостат, 19", 4U, RAL7035 for freestanding enclosures DS/DSZ and DSS	DLT44802-A
Странични панели за цокъл, D=1200, H=120 за DS/DSZ/DSI R7035	DSOT1220
Преден/задан панел за цокъл перф. + филтър, 600mm за DS Standschrank, RAL7035	DSOF1263
19" Аранжиращ панел с 5 метални пръстена, 1U, RAL7035	DBC14805
19" Аранжиращ панел с 5 големи пластм.пръстена, 1U, RAL7035	DBK14805
19" Фиксирана тава D=450mm, 80kg, 1U, RAL7035, перфорирана	DFS14845-C
19" Алюминиев профил PDU, 9шүко, 1U, 3м-кабел, RAL7035	IU070114-3
Разклонител за 19", 7 x Шүко с арестор, 1.25U, RAL7035 2m-connector cable, RAL7035	IU070113
19" Разклонител, 9xШүко, с ключ, 1U, 2м кабел, черно, ALU ALU Профил	Q7070114-A
19" Разклонител, 7xШүко, с ключ, 1U, защита от пренапрежение 2м-кабел, черен, ALU	Q7070113-A

Таблица с артикули

Описание	Артикулен No.
Акcesoари	
19" Монтажен комплект М6, 50 броя: винт, гайка, шайба	DSSRA050
19" mounting plate, 14U, sheet steel, perforated including screws and cage nuts	DMP1914
Осветителен модул LED, магнит, 230VAC, със сензор за врата автоматична функция, при отваряне на вратата, външен PSU	DTLIGHT01
Switch 24xRJ45 10/100/1000, Silent, w/o fan, internal PSU Metal-Chassis, 19"	QLGSW2457
Пач панел празен за 24 порта lightgrey, patchcord lock down	HSER0240GS