

Данни за артикула: DT478080-B

# Комуникационен шкаф стоящ S-RACK, W800 H2232 D800, 19", 47U

RAL9005 Black



## SCHRACK-Info

The S-RACK 19" freestanding network enclosure is the perfect solution for offices and similar environments. It is suitable for use as a central enclosure in network installations, but also as a sub-enclosure in the horizontal area of a structured cabling system.

The removable side and rear panels allow comfortable and easy access from all sides.

Cooling of the built-in components is achieved passively by heat exchange with the outside area and actively by optional roof fans.

Cable entry is very flexible due to various prepared opening possibilities or the optional base.

The S-RACK enclosures are designed for universal use and cover the widest possible range of applications.

- **Material thickness:**

- Top and bottom chassis: 1.5mm
- Corner profile: 1.2mm
- Rails: 1.5mm
- Front door (glass): 4.0mm
- Rear panel: 0.8mm
- Side panel: 0.8mm

- **Colours:**

- RAL9005 (black)
- Strips: RAL5005 (signal blue)

- **Height:** 47U

- **Width:** 800mm

- **Depth:** 800mm

- **Maximum load:** with even distribution: 800kg
- **Degree of protection:** IP20
- **Dismountability:** The individual parts of the cabinet are screwed. The enclosure is delivered assembled and can be partially or completely disassembled for transport to places that are difficult to access.
- **Doors:** Glass door including comfort swing handle with lock and keys. A conversion kit for half cylinders (DTZLOCK02) is optionally available. External hinge system allows door opening angle of up to 180°. Door hinged on the right. Conversion to left hinged door is possible. Glass door can be replaced by optionally available doors DTRT (full metal or perforated, full width or double door).
- **Side and back panels:** Removable side and back panels with lock and keys. Rear wall can be replaced by optionally available doors DTRT (glass, full metal or perforated, full width or double door).
- **Cable entry options:** In roof and floor. Fitted with plastic blank covers. The floor also accommodates a large break-out blank plate which can be easily removed for cable entry. Brush entry DTBB optionally available.
- **Cooling:** Passive cooling through heat exchange with the outside area. Ventilation slots on the roof are prepared for cooling. Active cooling through optional DTLT fan units.
- **Rails:** 19" rails (4 pieces), depth adjustable, U markings included
- **Accessories:** Numerous accessories (base sets, fans, shelves, cable management, doors, etc.) available
- **Earthing:** Earthing set is included
- **Levelling Feet:** Levelling Feet are included
- **Included mounting material:** 16 pieces cage nuts, screws and washers
- **Delivery:** Enclosure is delivered fully assembled on a throw-away pallet.



## Технически данни

|                               |                  |
|-------------------------------|------------------|
| Нето ширина (mm)              | 800,00           |
| Нето височина (mm)            | 2.232,00         |
| Дълбочина (mm)                | 800,00           |
| Нето тегло (kg)               | 94,60            |
| EAN                           | 9004840889802    |
| Мин. околна температура (°C)  | 5                |
| Макс. околна температура (°C) | 40               |
| HU                            | 47               |
| Цвят                          | RAL 9005 (black) |
| Степен на защита - IP         | IP20             |
| максимално натоварване (kg)   | 800              |
| Серия                         | S-RACK           |

## Таблица с артикули

| Описание                                                                                                                                                                                                      | Артикулен No. |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| Комуникационен шкаф стоящ S-RACK, W800 H2232 D800, 19", 47U<br>RAL9005 Black                                                                                                                                  | DT478080-B    |
| <b>Акcesoари</b>                                                                                                                                                                                              |               |
| Комплект основа 100mm за S-RACK, W=800 D=800, RAL9005<br>black                                                                                                                                                | DTOT10808B    |
| Таванен вент. модул 2 вент. за S-RACK, с аналогов термостат<br>Installation from outside of enclosure, for freestanding and wallmount enclosures                                                              | DTLTRO2A-B    |
| Таванен вент. модул 4 вент. за S-RACK, с цифров термостат<br>RAL9005, Installation from inside of enclosure. Suitable for 800, 1000 and 1200mm deep enclosures. Not recommended for<br>600mm deep enclosures. | DTLTRO4D-B    |
| Таванен вент. модул 4 вент. за S-RACK, с аналогов термостат<br>RAL9005, Installation from inside of enclosure                                                                                                 | DTLTRO4A-B    |
| Четка за кабелен вход за таван/под S-RACK стоящ шкаф<br>70x316mm                                                                                                                                              | DTZBRUSH02    |
| Четка за кабелен вход за таван/под S-RACK стоящ шкаф<br>70x500mm                                                                                                                                              | DTZBRUSH03    |
| Комплект дръжка за патрон полуцилиндър S-RACK<br>Стоящи шкафове                                                                                                                                               | DTZLOCK02     |
| Св. комплект за ком. табла DT, дълб. 800 и 1000mm, RAL9005<br>RAL9005, 1 set = 2 covers (for top and bottom) + 8x screws 6.3 x 12                                                                             | DTRA0800-B    |
| 19" Фиксирана тава, до 50kg товар, D=570mm, 1U, RAL9005<br>4 Point Fixing                                                                                                                                     | DTFF1570-B    |
| 19" Фиксирана тава, 1U, до 50kg товар, D=450mm, отворена<br>4 Point Fixing, RAL9005                                                                                                                           | DTFL1450-B    |
| 19" Аранжиращ панел, 1U, 5 метални пръстена, 63mm, RAL9005                                                                                                                                                    | DTBC105R-B    |
| 19" Аранжиращ панел, 1U, 5 метални пръстена, 130mm, RAL9005                                                                                                                                                   | DTBC105RGB    |
| К-т крепежни елементи за 19" M6, 50 винта, гайки и шайби                                                                                                                                                      | DTSRA050      |
| Осветителен модул LED, магнит, 230VAC, със сензор за врата<br>автоматична функция, при отваряне на вратата, външен PSU                                                                                        | DTLIGHT01     |
| Вертикален аранжиращ панел, метален за S-RACK 47U<br>1PU = 2Pieces, black RAL9005                                                                                                                             | DTKV47MS-B    |
| 19" Комплект за заземяване, 1U, 10 точки<br>4 броя x 4 мм в диаметър x 40 см дълги жълти / зелени проводници, включително винтове и гайки                                                                     | DTRE0001      |
| Пач панел 19" празен, 24 модула (SFA)(SFB), 1U, черен ECO<br>черно, единично закрепване, фиксиране на пач кабелите                                                                                            | HSE0240SP     |
| 19" Алюминиев профил PDU, 9хшuko, 1U, 3m-кабел, RAL7035                                                                                                                                                       | IU070114-3    |
| Разклонител за 19", 7 x Шuko с арестор, 1.25U, RAL7035<br>2m-connector cable, RAL7035                                                                                                                         | IU070113      |

## Таблица с артикули

| Описание                                                                              | Артикулен No. |
|---------------------------------------------------------------------------------------|---------------|
| <b>Акcesoари</b>                                                                      |               |
| 19" Разклонител, 9xШуко, с ключ, 1 U, 2m кабел, черно, ALU<br>ALU Профил              | Q7070114-A    |
| 19" Разклонител, 7xШуко, с ключ, 1 U, защита от пренапрежение<br>2m-кабел, черен, ALU | Q7070113-A    |
| Switch 24xRJ45 10/100/1000, Silent, w/o fan, internal PSU<br>Metal-Chassis, 19"       | QLGSW2457     |