

Данни за артикула: DTWE045445

19" Комуникационен шкаф стенен S-RACK, W=540 H=240 D=450, 4U

RAL7035 Light grey



SCHRACK-Info

Mainly used in offices and office-like environments, such as flats, single-family homes, etc. Suitable as a central distributor in small to medium-sized network installations, but also for use as a floor distributor (sub-distributor) in the horizontal area of structured cabling. The removable side panels allow convenient access to the installed components, even afterwards. For active cooling of the built-in components, optional DTLT fan units with one or two fans can be mounted in the roof.

- **Material:** Powder-coated steel sheet housing
- **Material thickness:**
 - Top and bottom chassis: 1.0mm
 - Corner profile: 1.0mm
 - Rails: 1.5mm
 - Front door (glass): 4.0mm
 - Rear panel: 1.0mm
 - Side panel: 0.8mm
- **Colour:**
 - RAL7035 (light grey)
 - Corner profile and rear panel: RAL5005 (signal blue)
- **Height:** 4U
- **Maximum load:** With even distribution: 80kg
- **Degree of protection:** IP20

- **Doors:** Glass door of safety glass 4mm including lock and 2 keys. Door hinged on the right. Conversion to left hinged possible. Opening angle of the door: approx. 200°.
- **Side panels:** removable and lockable
- **Rails:** 19" rails (2 pieces) in the front of the cabinet, galvanised, depth-adjustable
- **Cable entry options:** in roof and floor
 - The floor is provided with a plastic blank cover.
 - The roof is equipped with a brush entry.
- **Cooling:**
 - Passive cooling through ventilation slots and heat exchange with the outside area.
 - Active cooling by optional DTLT fans, which are easily and quickly inserted into the

Технически данни

Нето широчина (mm)	540,00
Нето височина (mm)	240,00
Дълбочина (mm)	450,00
Нето тегло (kg)	9,40
EAN	9004840880700
Мин. околна температура (°C)	5
Макс. околна температура (°C)	40
HU	4
Цвят	RAL 7035 / RAL 5005 (light grey / blue)
Степен на защита - IP	IP20
максимално натоварване (kg)	80
Серия	S-RACK

Таблица с артикули

Описание	Артикулен No.
19" Комуникационен шкаф стенен S-RACK, W=540 H=240 D=450, 4U RAL7035 Light grey	DTWE045445
Акcesoари	
Вентилаторен модул за таван 2вент.Аналогов термостат,RAL7035 Светлосиво, за стоящи и стенни шкафове	DTLTR02A
Вентилаторен модул за таван 2вент.ключ (on/off),RAL7035 Светлосиво, за стоящи и стенни шкафове	DTLTR02S
Вентилаторен модул за таван- 1вент.аналогов термостат,RAL7035 Светлосиво, за стоящи и стенни шкафове	DTLTR01A
Вентилаторен модул за таван 1вент. ключ(on/off), RAL7035 Светлосиво, за стоящи и стенни шкафове	DTLTR01S

Таблица с артикули

Описание	Артикулен No.
Акcesoари	
19" Фиксирана тава, 1U, до 30Kg товар, D=300mm, Нисък профил 2 точки на фиксиране, RAL7035	DTFT1300
Пач панел празен за 24 порта lightgrey, patchcord lock down	HSE0240GS
19" Аранжиращ панел за кабели, 1U, 5 метални пръстена, RAL7036	DTBC105R
К-т крепежни елементи за 19" M6, 20 винта, гайки и шайби	DTSRA020
Switch 24xRJ45 10/100/1000, Silent, w/o fan, internal PSU Metal-Chassis, 19"	QLGSW2457
19" Разклонител за 9xШуко, 1U, RAL7035	IU070114
Разклонител за 19", 7 x Шуко с арестор, 1.25U, RAL7035 2m-connector cable, RAL7035	IU070113
19" Разклонител, 9xШуко, с ключ, 1U, 2m кабел, черно, ALU ALU Профил	Q7070114-A
19" Разклонител, 7xШуко, с ключ, 1U, защита от пренапрежение 2m-кабел, черен, ALU	Q7070113-A