

Данни за артикула: HDCR100149

# IS-1 Комуник. шкаф IP54, със стр. панели, 80x130x80 RAL7035

Светло сиво



## SCHRACK-Info

With IP54 rating, specially designed for industrial applications and demanding environments. Provides protection from foreign bodies, splash water and spraying water from all directions. Perfectly suited to climate control and office solutions (sound insulation optional).

**Frame clearance at front:** 112mm**Static load capacity:** up to 18,000N**Material:**

Basic frame: 1.50mm steel sheet

Doors: 1.50mm steel sheet

Side panels: 1.50mm steel sheet

482.6mm (19") mounting angles: 2.00mm steel sheet

Glass: 3.00mm single pane safety glass

**Finish:**

Frame and cladding parts: powder-coated

Internal fittings: galvanised

**Equipment**

- basic frame, demountable, with integrated 25-mm mounting hole pitch pattern on all sides
- 4 galvanised 482.6mm (19") mounting angles with square perforations at the front and sides for cage nuts in acc. with IEC 297 d EIA, incl. height unit pitch pattern and labelling
- 1 front door, single wing with 3mm single pane safety glass, swing handle and profile half cylinder (30/10), EK333 lock and 4-point locking system

- 1 rear door, single wing steel sheet, solid, with swing handle and profile half cylinder (30/10), EK333 lock and 4- point locking system
- 2 side panels, screw fastened, two-section from depths of 1,000mm
- 1 top cover, single part, solid
- 1 Bottom cover panel
- 1 plinth, H 100mm, solid n 4 levelling feet, incl. protective caps
- 1 earthing set, mounted (all flat components earthed, central earthing point)

#### Inspections/Norms


Earthing in acc. with DIN VDE 0100-540

Components in acc. with IEC 297-1/2 (19")


## Технически данни

|                               |                       |
|-------------------------------|-----------------------|
| Нето широчина (mm)            | 800,00                |
| Нето височина (mm)            | 1.300,00              |
| Дълбочина (mm)                | 800,00                |
| Цвят                          | RAL 7035 (Light grey) |
| HU                            | 25                    |
| Нето тегло (kg)               | 124,00                |
| Мин. околна температура (°C)  | -10                   |
| Макс. околна температура (°C) | 60                    |

## Чертеж: IS-1 Комуник. шкаф IP54, със стр. панели, 80x130x80 RAL7035



**Чертеж: IS-1 Комуник. шкаф IP54, със стр. панели, 80x130x80 RAL7035**



Описание

Артикулен No.

IS-1 Комуник. шкаф IP54, със стр. панели, 80x130x80 RAL7035

HDCR100149

Светло сиво