

Данни за артикула: HSELS125TP

FO Пач панел, 12 влакна, ST, 50/ 125µm OM2, 19", 1U, ECO

acc. to IEC 61753-1, RAL7035, sliding



SCHRACK-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 24 ST / FC couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Технически данни

Оптика	50/125 OM2 Multimode
Цвят	RAL 7035 (Light grey)
Insertion loss typical (dB)	< 0,2
Return loss typical (dB)	> 35
Мин. околна температура (°C)	-10
Макс. околна температура (°C)	70
Оптичен брояч	12
Нето широчина (mm)	480,00
Нето височина (mm)	44,00
Нето тегло (kg)	2,53
Дълбочина (mm)	242,00

Таблица с артикули

Описание	Артикулен No.
FO Пач панел, 12 влакна, ST, 50/125µm OM2, 19", 1U, ECO acc. to IEC 61753-1, RAL7035, sliding	HSELS125TP
Акcesoари	
FO свиваем сплайс протектор 60mm	HELSP00011
FO свиваем сплайс протектор, 40mm	HELSP00010