

Данни за артикула: HSELS129LP

FO Пач панел, 12 влакна, LC, 9/125µm OS2, 19", 1U, ECO

IEC 61753-1, RAL7035, изваждаема



SCHRACK-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 LC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Технически данни

Нето ширина (mm)	480,00
Нето височина (mm)	44,00
Дълбочина (mm)	242,00
Нето тегло (kg)	2,53
Оптика	9/125 OS2 Singlemode / G.652.D
Цвят	RAL 7035 (light grey)
Insertion loss typical (dB)	< 0,2
Return loss typical (dB)	> 50
Мин. околна температура (°C)	-10
Макс. околна температура (°C)	70
Оптичен брояч	12

Таблица с артикули

Описание	Артикулен No.
FO Пач панел, 12 влакна, LC, 9/125µm OS2, 19", 1U, ECO IEC 61753-1, RAL7035, изваждаема	HSELS129LP
Акcesoари	
FO свиваем сплайс протектор 60mm	HELSP00011
FO свиваем сплайс протектор, 40mm	HELSP00010
Fiber Optics Cleaning Tool for LC and MU Suitable for UPC and APC connectors. More than 1,000 cleaning cycles.	HSELSZT001
FO Power meter with integrated laser light source (VFL) and RJ45-copper cable test. ATTENTION: This is a Laser Class 2 product. Do not stare into the beam. Always keep the cover on the VFL port when not in use. It is recommended to use laser safety glasses when working with fiber optic systems.	HSELSZT003
FO Пач кабел Duplex, LC/LC, 9/125µm OS2, жълт, 2.0m LSOH, yellow	HLP29LL02F
FO Пач кабел Duplex, LC/LC, 9/125µm OS2, жълт, 5.0m LSOH, yellow	HLP29LL05F

Таблица с артикули

Описание	Артикулен No.
Акcesoари	
FO Пач кабел Duplex, LC/SC, 9/125µm OS2, жълт, 2.0m LSOH, yellow	HLP29LC02F
FO Пач кабел Duplex, LC/SC, 9/125µm OS2, жълт, 5.0m LSOH, yellow	HLP29LC05F
FO Пач кабел Duplex, LC/FC, 9/125µm OS2, жълт, 2.0m LSOH, yellow	HLP29LF02F