




Данни за артикула: HSELS2400W

## FTTx Outdoor Splicebox WM empty for 24fibers, W200xH235xD67mm

RAL7035 Light grey, incl. three modular adapter plates with cutouts for FO-couplings: 12x LC-Dx, SC-Sx, or E-2000®-Sx with screws, 9x SC-Dx or 6x LC-QD with screws, 12x SC-Dx or LC-QD for snap-in mounting, 1 x set (30 pcs) shrink splice protection for crimp splice protection holders, IP54





## SCHRACK-Info

### Application

- Easy to mount splicebox for the indoor or outdoor construction of fibre optic distribution with the possibility of mounting a profile half cylinder
- Suitable for up to 24 optical fibres

### Technical Data

- Structured ASA (Acrylester-Styrol-Acrylnitril), extremely durable plastic, impact- resistant and weatherproof
- Cover locking by locking hooks with the option of sealing
- Splice cassette for easy installation and maintenance with maximum protection of the fibres with cross-out option and overlength tray
- Prepared for installation of profile half cylinder
- Strain relief for cables and patch cords
- Mounting option and fixation for gas - / water blockers available
- Patch cable outlet with flexible lamellar seal
- Modular adapter plate with cut-outs for fibre optic adapters included
  - Adapter plate 1: for up to 12x LC-Dx, SC-Sx or E-2000® -Sx
  - Adapter plate 2: for up to 9x SC-Dx or 6x LC-Quad
  - Adapter plate 3: for up to 12x SC-Dx, 6x LC-Quad without flange
- Equipped with 1x set (30 pcs) heat shrink splice protector for crimp splice holder
- Mounting option for 2x PCL splitter (40x4mm)
- Cable entry with 2x M20, 2x M25 cable gland possible
- Color: RAL7035 Light grey
- Protection class as per IEC 60529: IP54

### Climate area

- During transport: -25 °C bis +70 °C
- During installation: -5 °C bis +50 °C
- During operation: -5 °C bis +70 °C

### Mechanical Data

- Material: ASA, halogenfrei und schlagfest
- Dimensions:
  - Width: 200mm
  - Height: 235mm
  - Depth: 67mm
- Weight: 1,04kg

#### Accessories

- HSELSZSH12: FO shrink splice protector 45mm for FTTx Spliceboxes HSELS1200W / HSELS2400W
- DV900333--: Half cylinder lock keyed EK 333 including 1 key. (Countersunk screw M5x12mm is required)
- HSELSZMK01: Pole attachment for splicebox HSELSxx00W, diameter 60-215mm
- HSELSZMK02: Pole attachment for splicebox HSELSxx00W, diameter 60-325mm

#### Технически данни

|                               |        |
|-------------------------------|--------|
| Нето ширина (mm)              | 200,00 |
| Нето височина (mm)            | 235,00 |
| Дълбочина (mm)                | 67,00  |
| Нето тегло (kg)               | 1,04   |
| Мин. околна температура (°C)  | -5     |
| Макс. околна температура (°C) | 70     |

## Таблица с артикули

| Описание                                                                                                                                                                                                                                                                                                                                                           | Артикулен No. |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| FTTx Outdoor Splicebox WM empty for 24fibers, W200xH235xD67mm<br>RAL7035 Light grey, incl. three modular adapter plates with cutouts for FO-couplings: 12x LC-Dx, SC-Sx, or E-2000®-Sx with screws, 9x SC-Dx or 6x LC-QD with screws, 12x SC-Dx or LC-QD for snap-in mounting, 1 x set (30 pcs) shrink splice protection for crimp splice protection holders, IP54 | HSELS2400W    |
| <b>Акcesoари</b>                                                                                                                                                                                                                                                                                                                                                   |               |
| Pole attachment for splicebox HSELSxx00W, diameter 60-215mm<br>stainless steel, suitable for lamp poles or flag poles, incl. mounting material                                                                                                                                                                                                                     | HSELSZMK01    |
| Pole attachment for splicebox HSELSxx00W, diameter 60-325mm<br>stainless steel, suitable for lamp poles or flag poles, incl. mounting material                                                                                                                                                                                                                     | HSELSZMK02    |
| FO shrink splice protector 45mm, transparent, 1 PU=100 pcs.<br>for FTTx Outdoor Spliceboxes HSELS1200W / HSELS2400W                                                                                                                                                                                                                                                | HSELSZSH12    |
| Half cylinder lock keyed EK 333 including 1 key<br>including 1x countersunk screw M5x16mm V2A                                                                                                                                                                                                                                                                      | DV900333S     |