

Данни за артикула: HSELS245LP

FO Пач панел, 24 влакна, LC, 50/125µm OM2, 19", 1U, ECO

acc. to IEC 61753-1, RAL7035, sliding



SCHRACK-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 LC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Технически данни

Нето широчина (mm)	480,00
Нето височина (mm)	44,00
Дълбочина (mm)	242,00
Нето тегло (kg)	2,53
Цвят	RAL 7035 (Light grey)
Мин. околна температура (°C)	-10
Макс. околна температура (°C)	70
Insertion loss typical (dB)	< 0,2
Return loss typical (dB)	> 35
Оптика	50/125 OM2 Multimode
Оптичен брояч	24

Таблица с артикули

Описание	Артикулен No.
FO Пач панел, 24 влакна, LC, 50/125µm OM2, 19", 1U, ECO acc. to IEC 61753-1, RAL7035, sliding	HSELS245LP
Акcesoари	
FO свиваем сплайс протектор 60mm	HELSP00011
FO свиваем сплайс протектор, 40mm	HELSP00010
FO Пач кабел Duplex, LC/LC, 50/125µm OM2, оранжев, 2.0m	HLP25LL02F
FO Пач кабел Duplex, LC/LC, 50/125µm OM2, оранжев, 5.0m	HLP25LL05F
FO Пач кабел Duplex, LC/SC, 50/125µm OM2, оранжев, 2.0m	HLP25LC02F
FO Пач кабел Duplex, LC/SC, 50/125µm OM2, оранжев, 5.0m	HLP25LC05F
FO Пач кабел Duplex, LC / ST, 50/125µ, OM2, оранжев, 2.0m	HLP25LT02F
FO Пач кабел Duplex, LC / ST, 50/125µ, OM2, оранжев, 5.0m	HLP25LT05F