


Данни за артикула: HSFUBH089T

FO Унив. кабел A/I-DQ(ZN)BH 8x 9/125µm OS2, LS0H, Dca

С неметална защита от гризачи, черен, 6mm, 1250N, Drum 2100m



SCHRACK- Info

- For outdoor use in structured (data) wiring systems such as industrial backbone, campus backbone, building backbone (riser) and/or horizontal cabling. Support of all computer network applications, e.g. FDDI, Gigabit Ethernet and ATM.
- Suitable for direct burial.
- Easy to install in ducts, tunnels and trenches.

FEATURES AND BENEFITS

- Non-metallic rodent protection.
- Predicted lifetime > 30 years.



Технически данни

Оптичен брояч	8
Нето диаметър (мм)	5,80
Diameter - Central tube (мм)	3,30
Primary coating (µm)	250 ± 15
Нето тегло (кг.)	0,04
Подходящ	Universal cable

Технически данни - продължение

Watertightness	Yes
Rodent protection	Yes
Predicted lifetime	> 30 Години
Euroclass, съгласно EN50575	Dca
Smoke production	s2
Droplets	d1
Acidity	a1
Температурен обхват - Транспортиране / Съхранение (°C)	-30 to +70
Температурен обхват - при инсталиране (°C)	-5 to +50
Temperature range - Operation (°C)	-30 to +70
Pulling tension - Long term (N)	420
Pulling tension - Short term (N)	1250
Bending radii cable - Static (Ø)	10 x Ø
Bending radii cable - Dynamic (Ø)	20 x Ø
Bending radii for fibres and tubes (Ø)	> 25
Mode-Field / Cladding diameter (µm)	9,2 ± 0,4 125 ± 0,7
Wavelength (nm)	1310 1383 1550 1625
Attenuation (dB/km)	0,34 0,31 0,21 0,24
Dispersion (ps/nm-km)	≤ 3,5 ≤ 18
Ehternet performance 1GB (м.)	> 5000 - >70000 -
Ehternet performance 10GB (м.)	> 10000 - > 40000 -
PMD (ps/km)	≤ 0,2
Cable Cutt-off-Wavelength (nm)	≤ 1260
Refractive Index	1,467 - 1,467 1,467

GUIDE TO INSTALLATION AND HANDLING

- When laying and installing optical fibre cables it is vitally important not to exceed the specified values set for pulling tension, bending radii and temperature. The installation methods have to be in accordance with the common standards.
- To ease insertion into tubes by means of compressed air or pulling wire, certified lubricants (e.g. paraffin) may be used.
- The use of soap or similar substances as lubricants is strictly prohibited.
- If a cable needs to be fastened, constrictions > 0.3 mm must be prevented.
- The jelly filling inside the tubes can be removed using a tissue soaked in turpentine.
- It is advisable to cap the cable-ends during storage.

Таблица с артикули

Описание	Поръчка No.
FO Унив. кабел A/I-DQ(ZN)BH 8x 9/125µm OS2, LS0H, Dca	HSFUBH089T
С неметална защита от гризачи, черен, 6mm, 1250N, Drum 2100m	
Optional Accessories	
FO Пач панел, 8 влакна, LC, 9/125µm OS2, плъзгащ, 19", 1U	HSELS089LG
FO Пач панел, 8 влакна, SC, 9/125µm OS2, плъзгащ, 19", 1U	HSELS089CG
FO Пач панел, 8 влакна, FC,9/125µm OS2, плъзгащ, 19", 1U	HSELS089FG