

Данни за артикула: HVSMRJ5UWS

Кийстоун жак RJ45 неекраниран, Cat.5e (SFA)



SCHRACK-Info

TRANSMISSION PERFORMANCE

- Meet all requirements specified in connecting hardware requirement of ANSI/TIA-568-C.2, Category 5e

ELECTRICAL

- Electrical Insulation Resistance: 500MΩ min. 100VDC
- Dielectric Withstanding Voltage : 1000VDC or a.c. Peak Contact to Contact 60Hz for 1 minute

MECHANICAL

- Insertion / Extraction Life: 750 Cycles Minimum
- IDC Wire Gauge: 22 ~ 24 AWG

PHYSICAL

- Housing: High-Impact, Flame-Retardant Plastic, UL 94V-0
- Spring Wire: Phosphor Bronze Alloy Plated with 50μ-inch of Gold
- IDC: Phosphor Bronze Alloy with 100μ-inch 100% Sn Alloy



Технически данни

Технически данни - продължение

Нето широчина (mm)	16,90
Нето височина (mm)	21,90
Мин. околна температура (°C)	-10
Макс. околна температура (°C)	60

Таблица с артикули

Описание	NVP (%)	Тегло на медта (kg/km)	Артикулен No.
Кийстоун жак RJ45 неекраниран, Cat.5e (SFA)			HVSMRJ5UWS
Аксесоари			
Crimping Tool for HVSMRJ5UWS / HVSMRJ6UWS			HVSTOOL01S
U/UTP Кабел Cat.5e, 4x2xAWG24/1, PVC, син, 305m	69	15	HSEKU424P1
U/UTP Кабел Cat.5e, 4x2xAWG24/1, PVC, сив, 305m	69	15	HSEKU424P0
U/UTP Кабел Cat.5e, 4x2xAWG24/1, LS0H, син, 305m	69	15	HSEKU424H1
Пач панел празен за 24 порта lightgrey, patchcord lock down			HSER0240GS
Адаптер за DIN шина за 1 порт Lightgrey			HSERH010GS
Розетка TOOLLESS LINE, 1 порт, 80x80mm, наклонена, SFA/SFB pure white			HSED01UW2S
Розетка TOOLLESS LINE, 2 порта, 80x80mm, наклонена, SFA/SFB бяло			HSED02UW2S