

Данни за артикула: HVSMRJ6UBS

Jack RJ45 unshielded, Cat.6 (SFA) черно



SCHRACK-Info

TRANSMISSION PERFORMANCE

- Meet all requirements specified in connecting hardware requirement of ANSI/TIA-568-C.2, Category 6

ELECTRICAL

- Electrical Insulation Resistance: 500M Ω min. 100VDC
- Dielectric Withstanding Voltage : 1000VDC or a.c. Peak Contact to Contact 60Hz for 1 minute

MECHANICAL

- Insertion / Extraction Life: 750 Cycles Minimum
- IDC Wire Gauge: 22 ~ 24 AWG

PHYSICAL

- Housing: High-Impact, Flame-Retardant Plastic, UL 94V-0
- Spring Wire: Phosphor Bronze Alloy Plated with 50 μ -inch of Gold
- IDC: Phosphor Bronze Alloy with 100 μ -inch 100% Sn Alloy

Технически данни

Нето дължина (mm)	35,00
Нето ширина (mm)	17,00
Нето височина (mm)	26,00
Нето тегло (kg)	0,01
Мин. околна температура (°C)	-10

Технически данни - продължение

Макс. околна температура (°C)

60

Таблица с артикули

Описание	NVP (%)	Тегло на медта (kg/km)	Артикулен No.
Jack RJ45 unshielded, Cat.6 (SFA) черно			HVSMRJ6UBS
Акcesoари			
Crimping Tool for HVSMRJ5UWS / HVSMRJ6UWS			HVSTOOL01S
			HSEKU432P4
U/UTP Cable Cat.6, 4x2xAWG24/1, 300MHz, LS0H, Ecа, син Box 305m	69	18	HSEKU423H4
U/UTP Кабел Cat.6, 4x2xAWG24/1, 300MHz, LS0H, B2ca s1a,d1,a1, син	70	19	HSEKU423BB
Пач панел празен за 24 порта lightgrey, patchcord lock down			HSER0240GS
Адаптер за DIN шина за 1 порт Lightgrey			HSERH010GS