

Данни за артикула: IL954539--

# Метално табло Modul 2000, IP54, 400mm, 5A-39

RAL7035, 4 cutouts above



## SCHRACK-Info

- Wall-mounted frame with rear panel, 3-point rod lock with swing handle (prepared for half cylinder mounting)
- Material: 1.5 mm powder-coated sheet steel
- Phosphated, plastic powder-coated sheet steel enclosure tested and certified according to EN 62208:2011 and EN 60529:1991, protection class I suitable for TT/TN and IT network form, protection insulated according to ÖVE-IM 12
- Available in sizes from 2A/12 to 5A/42 Modul-high enclosures in the graded depths of 250, 300 and 400 mm
- Number of gland plates see technical table
- The cable entry can be made either from above or below, the cabinet can be rotated by 180 °. Supplied with blind flanges
- All components can be installed from standard Modul 2000
- It is also possible to use a mounting plate IL959xxx
- rated voltage Ue: 230/400V/50Hz
- rated insulation voltage Ui: 1000V
- rated impulse withstand voltage Uimp: 6kV
- rated short time withstand current Icw: 25kA / 1s
- rated peak withstand current Ipk: 54kA
- rated conditional short-circuit current Icc: 25kA
- Protective earth connection: Welded bolt M6,  $I^2t=3,6 \times 10^6 \text{ A}^2\text{s}$
- Protection class: I
- Ambient temperature: -5 to +40°C

- Relative humidity: 50% at +40°C
- Max. allowed load capacity: Use 150kg floor-mounted / Use 80kg wall-mounted (without additional supports) / door 10kg
- EMV: EMV Environment 1
- Degree of protection: IP54
- Impact resistance: IK08
- Color: RAL7035 (Light grey)



## Технически данни

|                        |                         |
|------------------------|-------------------------|
| Нето ширина (mm)       | 1.242,00                |
| Нето височина (mm)     | 1.900,00                |
| Дълбочина (mm)         | 400,00                  |
| Нето тегло (kg)        | 104,00                  |
| EAN                    | 9004840618716           |
| Разсейвана мощност (W) | -1033,00                |
| Тип                    | за монтаж на стена IP54 |
| Цвят                   | RAL 7035                |
| Ширина в модули        | 5                       |
| HU                     | 39                      |
| Степен на защита - IP  | IP54                    |
| Основно описание       | Рамка                   |

## Чертеж: Метално табло Modul 2000, IP54, 400mm, 5A-39



## Таблични файлове: Метално табло Modul 2000, IP54, 400mm, 5A-39

| Type                | Article number | Number of gland plates above | A<br>[mm] | B<br>[mm] | C<br>[mm] | D<br>[mm] | E<br>[mm] | Radiant power loss<br>[W]* |
|---------------------|----------------|------------------------------|-----------|-----------|-----------|-----------|-----------|----------------------------|
| <b>Depth 250 mm</b> |                |                              |           |           |           |           |           |                            |
| 2A12                | IL952212       | 2                            | 658       | 602       | 250       | 500       | 555       | -204                       |
| 2A18                | IL952218       | 2                            | 934       | 602       | 250       | 500       | 830       | -273                       |
| 2A21                | IL952221       | 2                            | 1072      | 602       | 250       | 500       | 970       | -307                       |
| 2A24                | IL952224       | 2                            | 1210      | 602       | 250       | 500       | 1105      | -342                       |
| 2A28                | IL952228       | 2                            | 1394      | 602       | 250       | 500       | 1290      | -387                       |
| 2A33                | IL952233       | 2                            | 1624      | 602       | 250       | 500       | 1520      | -445                       |
| 3A18                | IL952318       | 2                            | 934       | 822       | 250       | 720       | 830       | -343                       |
| 3A21                | IL952321       | 2                            | 1072      | 822       | 250       | 720       | 970       | -386                       |
| 3A24                | IL952324       | 2                            | 1210      | 822       | 250       | 720       | 1105      | -428                       |
| 3A28                | IL952328       | 2                            | 1394      | 822       | 250       | 720       | 1290      | -485                       |
| 3A33                | IL952333       | 2                            | 1624      | 822       | 250       | 720       | 1520      | -556                       |
| 4A21                | IL952421       | 3                            | 1072      | 1042      | 250       | 940       | 970       | -464                       |
| 4A24                | IL952424       | 3                            | 1210      | 1042      | 250       | 940       | 1105      | -515                       |
| 4A28                | IL952428       | 3                            | 1394      | 1042      | 250       | 940       | 1290      | -582                       |
| 4A33                | IL952433       | 3                            | 1624      | 1042      | 250       | 940       | 1520      | -667                       |
| 5A24                | IL952524       | 4                            | 1210      | 1242      | 250       | 1140      | 1105      | -594                       |
| 5A28                | IL952528       | 4                            | 1394      | 1242      | 250       | 1140      | 1290      | -671                       |
| 5A33                | IL952533       | 4                            | 1624      | 1242      | 250       | 1140      | 1520      | -768                       |
| <b>Depth 300 mm</b> |                |                              |           |           |           |           |           |                            |
| 2A39                | IL953239       | 2                            | 1900      | 602       | 300       | 500       | 1795      | -554                       |
| 2A42                | IL953242       | 2                            | 2038      | 602       | 300       | 500       | 1935      | -591                       |
| 3A39                | IL953339       | 2                            | 1900      | 822       | 300       | 720       | 1795      | -685                       |
| 3A42                | IL953342       | 2                            | 2038      | 822       | 300       | 720       | 1935      | -730                       |
| 4A39                | IL953439       | 3                            | 1900      | 1042      | 300       | 940       | 1795      | -815                       |
| 4A42                | IL953442       | 3                            | 2038      | 1042      | 300       | 940       | 1935      | -868                       |
| 5A39                | IL953539       | 4                            | 1900      | 1242      | 300       | 1140      | 1795      | -934                       |
| 5A42                | IL953542       | 4                            | 2038      | 1242      | 300       | 1140      | 1935      | -994                       |
| <b>Depth 400 mm</b> |                |                              |           |           |           |           |           |                            |
| 2A39                | IL954239       | 2                            | 1900      | 602       | 400       | 500       | 1795      | -636                       |
| 2A42                | IL954242       | 2                            | 2038      | 602       | 400       | 500       | 1935      | -678                       |
| 3A39                | IL954339       | 2                            | 1900      | 822       | 400       | 720       | 1795      | -773                       |
| 3A42                | IL954342       | 2                            | 2038      | 822       | 400       | 720       | 1935      | -823                       |
| 4A39                | IL954439       | 3                            | 1900      | 1042      | 400       | 940       | 1795      | -909                       |
| 4A42                | IL954442       | 3                            | 2038      | 1042      | 400       | 940       | 1935      | -967                       |
| 5A39                | IL954539       | 4                            | 1900      | 1242      | 400       | 1140      | 1795      | -1033                      |
| 5A42                | IL954542       | 4                            | 2038      | 1242      | 400       | 1140      | 1935      | -1099                      |

\* Max. radiated power of housing calculated as a wall-mounted single fixed with  $\Delta T = 35K$ .

Detailed information and legal notes see page 9

## Таблица с артикули

| Описание                                            | Артикулен No. |
|-----------------------------------------------------|---------------|
| Метално табло Modul 2000, IP54, 400mm, 5A-39        | IL954539      |
| RAL7035, 4 cutouts above                            |               |
| <b>Акcesoари</b>                                    |               |
| Скоби за стенен монтаж (2 броя), за Modul 2000 IP54 | IL900021-F    |

## Таблица с артикули

| Описание                                                                                                         | Артикулен No. |
|------------------------------------------------------------------------------------------------------------------|---------------|
| <b>Акcesoари</b>                                                                                                 |               |
| Фланец за кабелни вх. 2xM20, 8xM25/16, 4xM32/20, 1xM50/32<br>IP66                                                | IL958003-A    |
| Фланец за кабелни вхoдoвe 2xM16, 12xM20, 2xM40/25, 2xM50/32<br>IP66                                              | IL958004-A    |
| Преден / заден панел за основа, 5A / IP54, 1 брой                                                                | IL958500      |
| Комплект странични рамки за основа (2 бр.), 400mm<br>Подходящи за табла тип IP54 и IP20-C                        | IL091140      |
| Фланец за кабелни вхoдoвe (плътен), IP66                                                                         | IL958001-A    |
| Фланец за кабелни вхoдoвe, 4xM16, 6xM25/16, 8xM32/20                                                             | IL958002-A    |
| Фланец за кабелни вхoдoвe, IP66, 24xM16, 13xM20                                                                  | IL958005-A    |
| Фланец за кабелни вх, IP55, 44xØ3-14, 3xØ3-21, 2xØ3-30mm<br>foam-elastic                                         | IL958006-A    |
| Фланец за кабелни вхoдoвe, IP55, 9xØ3-20, 1xØ3-40, 2xØ3-70mm                                                     | IL958007-A    |
| Фланец за кабелни вхoдoвe, IP55, 7xØ3-20, 4xØ3-32, 3xØ3-50mm<br>foam-elastic                                     | IL958008-A    |
| Страничен панел 400mm, H=200mm, 1 к-т с включени винтове<br>inclusive Screws, for Modul 2000 Enclosures IL009xxx | IL090240      |