

Данни за артикула: INSNK021--

Допълнителен контакт NO, за 3P INSE, 40-63A

Snap-on N-contact for retrofitting a 3-pole switch to a 4-pole switch, Can only be used with a 40-63A INSE switch, not for use with INSR, INSP, and INSA!



Технически данни

Версия	аксесоари
Номинален ток (A)	63
Полюси	1
Монтаж	surface mounting
Standard	IEC 60947, EN 60947, VDE 0666
Rated insulation voltage [Ui] (V)	690
Rated impulse withstand voltage [Uimp] (V)	6000
Rated short-time withstand current Icw	1000
Rated conditional short-circuit-current	10kA @ 440V / 6kA @ 690V
Short-circuit protection maximum fuse	63
Честота (Hz)	50/60


Технически данни - продължение

Operating Current	AC-22A - 690V - 63A AC-3 - 690V - 17A AC-3 - 230V - 38A AC-23A - 400V - 41A AC-23A - 690V - 21A AC-21A - 690V - 63A AC-3 - 400V - 36A AC-23A - 230V - 38A
Switching Capacity	AC-3 - 690V - 15kW AC-23A - 230V - 11kW AC-23A - 400V - 22kW AC-23A - 690V - 18.5kW AC-3 - 230V - 11kW AC-3 - 400V - 18.5kW
According to UL 508 / CSA	
Начин на свързване	UL/CSA - AWG 14-6
Оперативно напрежение AC (V)	600
Thermal rated continuous current (A)	63
Active Power	3x240VAC - 15Hp 3x120VAC - 5Hp 3x480VAC - 25Hp 1x240VAC - 10Hp 3x600VAC - 30Hp 1x120VAC - 3Hp
Свързване	
Conventional thermal current Ith (A)	63
Tightening torque (Nm)	3
Connection cross-section, multi-wire (mm ²)	2,5-16
Connection cross section, single wire (mm ²)	2,5-16
Connection cross-section, flexible wire with ferrule (mm ²)	2,5-16
Retrofit contacts	
Neutral conductor contacts	Neutral conductor early-make, late-break design (closes before and opens after the phase conductors to prevent voltage displacement) As soon as a 3-pole switch is converted to a 4-pole switch using a neutral conductor contact, NO additional auxiliary contact is permitted to be attached to the neutral conductor contact! For further information, see the data sheet for the respective switch.
Работна температура	-25°C to +55°C
Mechanical durability	100000 switching cycles
Power loss per pole (W)	3,60
Protection against direct contact	finger-proof and back-of-hand-proof according to VDE 0106 Part 100
Степен на защита - IP	IP65 (front), IP20 (terminals)
Lockable	No
Нето дължина (mm)	73,00

Технически данни - продължение

Нето ширина (mm)	18,30
Нето височина (mm)	44,00
Мин. околна температура (°C)	-25
Макс. околна температура (°C)	55

Чертеж: Допълнителен контакт NO, за 3P INSE, 40-63A



Описание	Артикулен No.
Допълнителен контакт NO, за 3P INSE, 40-63A Snap-on N-contact for retrofitting a 3-pole switch to a 4-pole switch, Can only be used with a 40-63A INSE switch, not for use with INSNK021 INSR, INSP, and INSA!	