

Данни за артикула: IU070112--

19" Разклонител за 6xШуко с ДТЗ

BO217516, 1U

2m-connector cable, RAL7035



SCHRACK-Info

Sockets:

- 6x CEE 7/3 (Type F)
- DIN 49440, eximinated: VDE0620-1;
- 2-pole with earthing contact;
- 16A/3680W, AC250V, IP20;
- colour similär RAL7035, 35° turned

Connection:

- non rewirable, Endcaps riveted, inside wiring without euro terminal
- 22,0m H05VV-F 3G1,5mm² black with right angled plug with earthing contact

Profile:

- 1U, ALU anodised
- Length: 438,5mm

Plastic material:

- RAL7035, PA6, fibre glass 30%, Glow wire test up to 850°C; V1

Extent of delivery:

- 1x Socket outlet

- 2x Mounting brackets

Overcurrent protection with residual current circuit breaker (RCBO):

- Rated voltage: 230V~
- Rated current: 16A
- Rated residual current: $\leq 30\text{mA}$
- Pole number: 2
- Tripping characteristic: C
- RCD type: AC
- RCD construction type: G (short-time delayed)

Технически данни

Нето ширина (mm)	483,00
Нето височина (mm)	44,00
Дълбочина (mm)	60,00
Нето тегло (kg)	1,00
Мин. околна температура (°C)	5
Макс. околна температура (°C)	45
Цвят	RAL 7035 (Light grey)

Таблица с артикули

Описание	Артикулен No.
19" Разклонител за 6xШуко с ДТЗ BO217516, 1U 2m-connector cable, RAL7035	IU070112
Акcesoари	
PDU-държач вертикален за 800 mm широки DS и DSZ-кутии, 1U 1 PU = 2 pcs., Installation on vertical rail, Assembly material included	DSPDU010
PDU-държач вертикален за 600 и 800 mm широки DSS-кутии DST- Enclosures, 1U, 1 PU = 2 pcs. For PDUs with 19" style mounting holder. Installation in enclosure skeleton. Assembly material included	DSSPDU010
PDU-държач вертикален за 600 и 800 mm широки DSS-кутии DST- Enclosures, 2U, 1 PU = 2 pcs. For PDUs with 19" style mounting holder. Installation in enclosure skeleton. Assembly material included	DSSPDU021
Захранващ кабел - C13, черен, 1,8m	Q7130121
Захранващ кабел - C13, черен, 3m	Q7130059
Захранващ Кабел, Schuko, 90° - 5m	Q7170732
Захранващ кабел, Euro 8 - 1.8m	Q7172506
Захранващ кабел - C5 (триъгълник), черен, 1.8m	Q7172902