

Данни за артикула: IUKTI6401 -

Климатик 2000W, частично вгр. монтаж към табло, Серия DTI

400V, Installation depth=120mm, IP55, RAL 7035



SCHRACK-Info

General:

- Cooling unit for partially recessed mounting (=DTI)
- For door or side mounting
- Technical design with a standard controller
- Color: RAL 7035 (Light grey)

Green Series Cooling Unit:

- Highest energy efficiency for significant energy savings and operating cost reduction
- Significantly less refrigerant used
- UL listed according to UL 60335 for long-term planning even after 2024
- Large distance between intake and exhaust vents, safe circulation within the electrical enclosure due to long passage of air, therefore hot spots are eliminated
- Exceptional serviceability

IUKTI6401:

- Cooling performance: 2000W
- Rated voltage: 400V
- Type of connection: Spring-type terminal included with plug

- Installation depth: 120mm
- Degree of protection IP55: Towards the enclosure
- Degree of protection IP24: Towards the surroundings




Технически данни

Нето ширина (mm)	485,00
Нето височина (mm)	1.537,00
Дълбочина (mm)	278,00
Нето тегло (kg)	63,00
Мин. околна температура (°C)	10
Макс. околна температура (°C)	55
Степен на защита - IP	IP55
Клас на защита	I
Номинално напрежение	400V-AC
Тип	климатик
мощност на охлаждане (W)	2000


Таблични файлове: Климатик 2000W, частично вгр. монтаж към табло, Серия DTI

Daten	Einheit	IUKTI6401
Nennspannung +10%	Hz V	AC 50 / 60 400 / 460 3~
Kälteleistung L35/L35: nach EN 14511 L35/L50:	W	2000 1500
Leistungsaufnahme L35/L35:	W	727 / 911
Einschaltstrom L35/L35:		7,7
Kälteleistungszahl ϵ_{ke}		2,75
Luftvolumenstrom intern	m³/h	1175
freiblasend extern	m³/h	945
Absicherung T	A	4
Anschlussart		Federzugklemme an beigefügtem Stecker
Umgebungstemperatur	°C (°F)	+10 bis +55 (+50 bis +131)
Regelbereich (einstellbar)	°C (°F)	+25 bis +45 (+77 bis +113)
Kältemittel R134a	g	500
Kondensatabscheidung		integrierte Kondensatverdunstung mit Sicherheitsüberlauf
Schutzart IP55		gegenüber dem Schaltschrank, bei bestimmungsgemäßem Einsatz
nach EN 60529 IP24		gegenüber der Umgebung, bei bestimmungsgemäßem Einsatz
Bauweise Gehäuse		Stahlblech verzinkt
Haube		elektrostatisch pulverbeschichtet (200 °C)
Abmessungen	[mm]	H=1540, B=485, T=278
Nettogewicht	[kg]	63
Farbe		RAL 7035 (Lichtgrau)

Cooling Capacity Performance Curves



Dimensions and Cutout IUKTI6401



Описание	Артикулен No.
Климатик 2000W, частично вгр. монтаж към табло, Серия DTI 400V, Installation depth=120mm, IP55, RAL 7035	IUKTI6401