

Данни за артикула: LID17787--

Linear BU LED 20-40W 3K/4K/5K CRI90 IP20 UGR17 230V черно

Direct (20/30/40W) 34° / indirect (16/20/25W) 120°, 3m cable; CCTV PV 230V DARK LIGHT; 11 OFFICE & KITCHEN



Информация за продукта

CCT and Power variable 40W UGR17 Linear system with with 48 LED spots and uplight for suspended installation, ideal for offices. Complete with 2 x power variable drivers. Complies with standard EN60598-1 and any other specific standards.

Технически данни

Нето дължина (mm)	1.300,00
Нето ширина (mm)	35,00
Нето височина (mm)	70,00
Цвят	Черно
Материал	Алуминий
Ъгъл на излъчване (°)	34/120
Glare factor (UGR)	<17
Контролер	LED контролер
Оперативно напрежение AC (V)	220-240
Входно напрежение AC (V)	220-240
Фасунга	LED Platine
Ефективност на системата (lm/W)	95

Технически данни - продължение

Мощност (W)	40 30 20
Цвят на светлината	neutral white топло бяла cool white
Цветна температура (K)	5000 4000 3000
Индекс на цветоподаване	≥90
Светлинен поток (lm)	max. 1800/3800
Димируем	не
Клас на защита	I
Степен на защита - IP	IP20
Диаметър, mm (mm)	68
ДхШхВ mm	1300x35x70

Чертеж: Linear BU LED 20-40W 3K/4K/5K CRI90 IP20 UGR17 230V черно



Описание	Артикулен No.
Linear BU LED 20-40W 3K/4K/5K CRI90 IP20 UGR17 230V черно Direct (20/30/40W) 34° / indirect (16/20/25W) 120°, 3m cable; CCTV PV 230V DARK LIGHT; 11 OFFICE & KITCHEN	LID17787