

Данни за артикула: NLCC24-20-

Маломощна система CoreCompact24, 24V АС, 4/20

4 electrical circuits, max. 80 luminaires (20 luminaires per circuit), max. power rating: 250W
1h / 97W 3 h / 30W 8 h, optionally: Battery extension (NLBALI020), h x w x d: 455 x 250
x 230 mm



Технически данни

Нето дължина (mm)	230,00
Нето ширина (mm)	250,00
Нето височина (mm)	455,00
Нето тегло (kg)	13,00

Таблица с артикули

Описание	Артикулен No.
Маломощна система CoreCompact24, 24V AC, 4/20 4 electrical circuits, max. 80 luminaires (20 luminaires per circuit), max. power rating: 250W 1h / 97W 3 h / 30W 8 h, optionally: NLCC24-20 Battery extension (NLBALI020), h x w x d: 455 x 250 x 230 mm	
Акcesoари	
E30 fire protection panel for LPS MicroControl MI with fan Outside dimensions: 918 x 711 x 345mm (HxWxD), colour RAL7035, 105kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30, for LPS MicroControl with 7Ah or 9Ah battery set and for LPS CoreCompact 24 with 40Ah battery set	NLMIE30A
Индикаторен панел с LED For 24V AC LPS systems Core 24	NLCMA
Разширение за батерия, CC24 LiFePO4 19.8Ah incl. connection cable for 2 batteries	NLBALI020