

Данни за артикула: NLPXWT433W

Emergency luminaire PX WirelessControl ERT-LED 3h 230V AC TT

Exit sign: wall surface mounting, safety light: ceiling surface mounting, viewing distance: 30m, radio switchable, 520lm, LiFePO4 battery suitable for low temperatures -15° to 40°C, 520lm



Технически данни

Нето дължина (mm)	340,00
Нето ширина (mm)	60,00
Нето височина (mm)	170,00
Нето тегло (kg)	0,90
Тип осветително тяло	комб. аварийни и RZ осветители авариен осветител
Автономност - централна бат.	Self contained luminaire
Функция	WirelessControl Low Temperature
Версия	пластмасов осветител
Дизайн	PX
Безхалогенен	Housing made of halogen-free plastic
Цвят	RAL 9003 (white)

Технически данни - продължение

Pictogram	Slide-in pictogram set (2x man in the door and one arrow that can be rotated by 90°) included in accordance with ISO 7010
Визуален обхват (m)	30
Време на съхранение (h)	3
Осветеност	ERT-LED (4W)
Лумен	520
MPP диапазон на напрежение (V)	230V AC 50Hz ±20%
Power maintained mode (W)	5,70
Power non-maintained mode (W)	0,80
Power max. (W)	7,50
Батерия (V/Ah)	2x 3,2V/3,3Ah LiFePO4-TT
Степен на защита - IP	IP65
Impact Resistance	IK05
Монтаж	surface mounting ceiling универсален surface mounting wall recessed mounting ceiling optional
Мин. околна температура (°C)	-15
Макс. околна температура (°C)	40
AA Class E 8101	AA4
Производител	Schrack

Spacing table with square lens (for optimized illumination of the pictogram) (included in scope delivery) - Minimum illuminance on the centerline at +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 1h/3h

					
2,00	5,03	11,47	11,47	11,47	5,03
2,50	5,75	13,22	13,22	13,22	5,75
3,00	6,35	14,79	14,79	14,79	6,35
3,50	6,59	16,2	16,2	16,2	6,59
4,00	6,69	17,48	17,48	17,48	6,69
5,00	4,78	18,72	18,72	18,72	4,78
6,00	2,9	17,57	17,57	17,57	2,9

Spacing table with corridor lens (NLLSYSF4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 1h/3h

					
2,00	5,41	12,15	10,43	8,84	3,68
2,50	6,51	14,33	12,02	9,84	4
3,00	7,51	16,36	13,52	10,71	4,2
3,50	8,44	18,55	14,73	11,34	4,34
4,00	9,3	20,61	16,07	11,78	4,43
5,00	10,86	24,4	18,29	12,37	4,4
6,00	8,41	27,81	20,14	12,65	4,29
7,00	6,41	26,48	18,47	12,49	4,18
8,00	4,79	26,58	16,62	12,3	3,87
9,00	2,76	23,86	14,84	12,13	3,03

Spacing table with round lens (NLLSYSR4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 1h/3h

					
2,00	4,21	9,38	9,38	9,38	4,21
2,50	5,05	10,9	10,9	10,9	5,05
3,00	5,81	12,56	12,56	12,56	5,81
3,50	6,51	14,22	14,22	14,22	6,51
4,00	7,14	15,77	15,77	15,77	7,14
5,00	7,55	18,58	18,58	18,58	7,55
6,00	4,89	19,41	19,41	19,41	4,89
7,00	3	18,4	18,4	18,4	3

Spacing table with spot lens (NLLSYSS4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 1h/3h

					
2,00	1,91	4,79	4,79	4,79	1,91
2,50	2,39	5,99	5,99	5,99	2,39
3,00	2,87	7,19	7,19	7,19	2,87
3,50	3,33	8,39	8,39	8,39	3,33
4,00	3,57	8,74	8,74	8,74	3,57
5,00	4,04	9,53	9,53	9,53	4,04
6,00	4,51	10,45	10,45	10,45	4,51
7,00	4,88	11,4	11,4	11,4	4,88
8,00	5,26	12,39	12,39	12,39	5,26
9,00	5,56	13,23	13,23	13,23	5,56
10,00	5,78	13,93	13,93	13,93	5,78
12,00	6,02	15,36	15,36	15,36	6,02
14,00	5,98	16,35	16,35	16,35	5,98
16,00	5,67	16,93	16,93	16,93	5,67

Spacing table with high corridor lens (NLLSYSH4 must be ordered separately)
- Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 -
Autonomy time 1h/3h

					
2,00	2,2	5,89	7,64	9,38	4,09
2,50	2,75	7,36	9,55	11,73	5,12
3,00	3,28	8,73	11,31	13,87	6,05
3,50	3,34	9,06	12,13	15,12	6,7
4,00	3,35	9,27	12,88	16,55	7,29
5,00	3,27	9,5	14,34	19,2	8,23
6,00	2,74	9,51	15,51	21,52	8,89
7,00	2,57	9,35	16,35	23,36	9,38
8,00	2,65	8,59	16,65	24,76	9,72
9,00	2,66	7,66	16,65	25,97	9,9
10,00	2,62	7,25	16,9	26,85	9,98
12,00	2,62	7,55	16,92	28,07	8,99
14,00	2,39	7,41	15,75	28,23	8,54
16,00	1,98	7,5	15,31	26,42	7,13

Таблица с артикули

Описание	Артикулен No.
Emergency luminaire PX WirelessControl ERT-LED 3h 230V AC TT Exit sign: wall surface mounting, safety light: ceiling surface mounting, viewing distance: 30m, radio switchable, 520lm, LiFePO4 battery suitable for low temperatures -15° to 40°C, 520lm	NLPXWT433W
Акcesoари	
Rain cover for emergency luminaires design KC plexiglass	NLKCRD
Сферична защитна кошница за KC, KL, PF, S8, LX, SB, SY, TX l x h x d: 450 x 280 x 125mm	NLBALL2
Pictogram set for NLPX.. 2x wheelchair, 2x arrows diagonal 2 part pictograms, vd: 30m	NLPXPIKTO2
	NLTESTSC2
Protective cover for test buttons NLTEST2---	NLTEST2COV
Батерия LiFePO4 3.2V 3.3Ah за LED осв., KM, KSC, KMB, ASM, ZAW LiFePO4 - Lithium-iron-phosphate battery suitable for low temperatures, UN3480 - LITHIUM-ION BATTERIES, The permissible ambient luminaire temperatures are specified for the low temperature luminaires	NLAKKU323T