

Данни за артикула: NLPXWT438W

Emergency luminaire PX WirelessControl ERT-LED 8h 230V AC TT

Exit sign: wall surface mounting, safety light: ceiling surface mounting, viewing distance: 30m, radio switchable, 520lm, LiFePO4 battery suitable for low temperatures -15° to 40°C, 245lm



Технически данни

Нето дължина (mm)	340,00
Нето ширина (mm)	60,00
Нето височина (mm)	170,00
Нето тегло (kg)	0,90
Тип осветително тяло	авариен осветител
Автономност - централна бат.	Self contained luminaire
Функция	WirelessControl Low Temperature
Версия	пластмасов осветител
Дизайн	PX
Безхалогенен	Housing made of halogen-free plastic
Цвят	RAL 9003 (white)
Pictogram	Slide-in pictogram set (2x man in the door and one arrow that can be rotated by 90°) included in accordance with ISO 7010

Технически данни - продължение

Визуален обхват (m)	30
Време на съхранение (h)	3
Осветеност	ERT-LED (4W)
Лумен	245
MPP диапазон на напрежение (V)	230V AC 50Hz $\pm 20\%$
Power maintained mode (W)	5,70
Power non-maintained mode (W)	0,80
Power max. (W)	7,50
Батерия (V/Ah)	2x 3,2V/3,3Ah LiFePO4-TT
Степен на защита - IP	IP65
Impact Resistance	IK05
Монтаж	surface mounting ceiling универсален surface mounting wall recessed mounting ceiling optional
Мин. околна температура (°C)	-15
Макс. околна температура (°C)	40
AA Class E 8101	AA4
Производител	Schrack

Spacing table with square lens (for optimized illumination of the pictogram) (included in scope delivery) - Minimum illuminance on the centerline at +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 8h

					
2,00	4,29	9,95	9,95	9,95	4,29
2,50	4,55	11,35	11,35	11,35	4,55
3,00	4,29	12,42	12,42	12,42	4,29
3,50	3,11	12,87	12,87	12,87	3,11
4,00	2,16	12,25	12,25	12,25	2,16

Spacing table with corridor lens (NLLSYSF4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 8h

					
2,00	4,93	10,84	8,98	7,23	2,84
2,50	5,84	13,01	10,28	7,84	2,97
3,00	6,67	14,99	11,54	8,22	3,03
3,50	7,22	16,82	12,58	8,48	2,99
4,00	5,37	18,52	13,5	8,63	2,94
5,00	3,93	17,81	11,74	8,46	2,8
6,00	2,21	16,25	10,3	8,3	2,25

Spacing table with round lens (NLLSYSR4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 8h

					
2,00	3,89	8,38	8,38	8,38	3,89
2,50	4,58	10,05	10,05	10,05	4,58
3,00	5,19	11,54	11,54	11,54	5,19
3,50	5,15	12,91	12,91	12,91	5,15
4,00	3,83	13,42	13,42	13,42	3,83
5,00	1,54	12,54	12,54	12,54	1,54

Spacing table with spot lens (NLLSYSS4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 8h

					
2,00	1,91	4,79	4,79	4,79	1,91
2,50	2,31	5,8	5,8	5,8	2,31
3,00	2,53	6,08	6,08	6,08	2,53
3,50	2,78	6,57	6,57	6,57	2,78
4,00	3,02	7,04	7,04	7,04	3,02
5,00	3,41	7,99	7,99	7,99	3,41
6,00	3,75	8,91	8,91	8,91	3,75
7,00	3,98	9,64	9,64	9,64	3,98
8,00	4,1	10,37	10,37	10,37	4,1
9,00	4,12	10,93	10,93	10,93	4,12
10,00	4,05	11,34	11,34	11,34	4,05
12,00	3,59	11,7	11,7	11,7	3,59
14,00	2,56	11,53	11,53	11,53	2,56

Spacing table with high corridor lens (NLLSYSH4 must be ordered separately)
- Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 -
Autonomy time 8h

					
2,00	2,2	5,84	7,56	9,25	4,02
2,50	2,27	6,2	8,38	10,56	4,66
3,00	2,27	6,4	9,19	11,98	5,22
3,50	2,19	6,5	9,87	13,25	5,61
4,00	1,95	6,5	10,45	14,4	5,95
5,00	1,77	6,28	11,23	16,18	6,41
6,00	1,83	5,31	11,34	17,46	6,67
7,00	1,81	5,01	11,53	18,35	6,6
8,00	1,81	5,17	11,54	18,98	6,12
9,00	1,73	5,14	10,85	19,27	5,89
10,00	1,58	5,13	10,53	18,88	5,61
12,00	1,02	5,05	9,65	17,18	3,55

Таблица с артикули

Описание	Артикулен No.
Emergency luminaire PX WirelessControl ERT-LED 8h 230V AC TT Exit sign: wall surface mounting, safety light: ceiling surface mounting, viewing distance: 30m, radio switchable, 520lm, LiFePO4 battery suitable for low temperatures -15° to 40°C, 245lm	NLPXWT438W
Акcesoари	
Rain cover for emergency luminaires design KC plexiglass	NLKCRD
Сферична защитна кошница за KC, KL, PF, S8, LX, SB, SY, TX l x h x d: 450 x 280 x 125mm	NLBALL2
Pictogram set for NLPX.. 2x wheelchair, 2x arrows diagonal 2 part pictograms, vd: 30m	NLPXPIKTO2
	NLTESTSC2
Protective cover for test buttons NLTEST2---	NLTEST2COV
Батерия LiFePO4 3.2V 3.3Ah за LED осв., KM, KSC, KMB, ASM, ZAW LiFePO4 - Lithium-iron-phosphate battery suitable for low temperatures, UN3480 - LITHIUM-ION BATTERIES, The permissible ambient luminaire temperatures are specified for the low temperature luminaires	NLAKKU323T