

Данни за артикула: QLIES0820-

DIN-Rail Switch 8xRJ45, без захранване

8 x 10/100Mbps, input voltage 12VDC-56VDC



SCHRACK-Info

The industrial 8 port Ethernet switch is equipped with 8 port 10/100Mbps Ethernet ports. It is designed for 12-56VDC input sources, especially for IP surveillance, traffic monitoring and for a broad range of applications. It can be used as a stand-alone device for buses, trucks and other vehicles for Surveillance purposes. It is being rigorously tested for your Security, Transportation and Telco application.

Key-Features

- Provides flexibility of 8 x 10/100BASE-TX ports
- Offers DIN rail or panel mounting
- Operating temperature range of -40°C to 75°C
- Supports 12 to 56 VDC power inputs
- Redundant power inputs with terminal block

TECHNICAL DATA

- Approvals and conformity
 - FCC Part 15 Subpart B Class A, CE, VCCI, IEC EN60950-1, IEC 60068-2-27, IEC 60068-2-6
- Max. Operating Humidity
 - 95%
- Max. Operating Temperature
 - 75°C
- Min. Operating Humidity

- 5%
- Min. Operating Temperature
 - -40°C
- Backplane (Gbps)
 - 1.6 Gbit/s
- Indicators
 - PW1(Power 1) Green
 - PW2(Power 2) Green
 - SW(relay) Amber
 - TX/RJ-45 port: LNK (Link/Active) Green
- MAC Address Table
 - 1K
- Mount
 - DIN rail mount
- Output voltage
 - Relay outputs with current carrying capacity of 1 A @24VDC
- Power supply
 - Optional
- Standards
 - IEEE 802.3 10Base-T Ethernet
 - IEEE 802.3u 100Base-TX Fast Ethernet
 - IEEE802.3x Flow Control and Back Pressure
- Product weight
 - 0,73 kg
- Product width
 - 142 mm
- Product depth
 - 105 mm
- Product height
 - 36,2 mm
- Color
 - Black
- EAN
 - 4015867181546
- Model number
 - QLIES0820-
- PoE Supported
 - None
- Concurrent ports
 - 8.00 Total

- Energy consumption
 - 3W @ 48VDC full load

Package Contents

- QLIES0820-
- Wall-Mounting set
- DIN rail mounting set
- High current terminal block

Технически данни

Нето широчина (mm)	142,00
Нето височина (mm)	36,20
Дълбочина (mm)	105,00
EAN	4015867181546
Мин. околна температура (°C)	-40
Макс. околна температура (°C)	75
Продукт	Етернет комунтатори(суичове)
Скорост	10/100Mbps
портове	8
Монтаж	DIN релса

Таблица с артикули

Описание	Артикулен No.
DIN-Rail Switch 8xRJ45, без захранване 8 x 10/100Mbps, input voltage 12VDC-56VDC	QLIES0820
Акcesoари	
Адаптер за DIN шина за 1 порт Lightgrey	HSERH010GS
Захранване индустриален тип, 24VDC, 30W, за DIN-релса	QLPOW2410
Захранване индустриален тип, 24VDC, 60W, за DIN-релса	QLPOW2420
Захранване индустриален тип, 24VDC, 75W, за DIN-релса	QLPOW2430
Захранване индустриален тип, 24VDC, 120W, за DIN-релса	QLPOW2440
Захранване индустриален тип, 48VDC, 120W, за DIN-релса PoE Ready	QLPOW4840
Захранване индустриален тип, 48VDC, 240W, за DIN-релса PoE Ready	QLPOW4850
Захранване индустриален тип, 48VDC, 480W, за DIN-релса PoE Ready	QLPOW4860
Захранване, 110V-240VAC 50/60Hz ; 48VDC/1.35A, 64,8W	QLPOW4801