

Данни за артикула: SR3PDIEM06

PDU Essential Metered; 24xC13; 6xC19; 400V; 16A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 16A/400V | 11 kW
- Output: 24xC13 0° IEC Socket 6xC19 90° IEC Socket
- split into three phases
- Supply cable: 3.0m | 2,5mm²
- with CEE 16A plug, red
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Технически данни

Нето дължина (mm)	1.458,60
Нето ширина (mm)	45,00
Нето височина (mm)	60,00
Нето тегло (kg)	1,90
EAN	4057298233074
ЦЕНА	1.297,00
Мин. околна температура (°C)	-5
Макс. околна температура (°C)	45
Номинално напрежение	400V
Степен на защита - IP	IP20
Тип продукт	Metered Essential
Number of sockets	30
Outlet type	24 x IEC320 C13 und 6 x IEC320 C19
Номинален ток (A)	16
Phases per feed	3
Начин на свързване	CEE 16 A red
Protocol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Монтаж	Bracket (L-shape)

Описание	Артикулен No.
PDU Essential Metered; 24xC13; 6xC19; 400V; 16A	SR3PDIEM06
Measurement per phase, incl. mounting bracket with screws	