

Данни за артикула: SR3PDIPM11

PDU PRO Metered, 24xC13, 6xC19, 400V, 32A, RCM

Measurement per phase, Residual Current Monitoring per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!



SCHRACK-Info

- PDU PRO Metered RCM
- Residual Current Monitoring per phase, Typ B
- Metering per phase
- Input: 32 A / 400 V | 22 kW
- Supply cable: 3,0 m | 4 mm²
- with CEE plug 32 A red
- Output: 24x C13 IEC Socket + 6 x C19 IEC Socket
- 6x hydraulic-magnetic circuit breakers 16 A
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)

- Incl. mounting brackets (L-shaped)
- Packed in cardboard box
- Length 1896 mm

Технически данни

Нето дължина (mm)	1.927,80
Нето ширина (mm)	56,00
Нето височина (mm)	65,00
EAN	4057298207952
ЦЕНА	3.097,00
Мин. околна температура (°C)	0
Макс. околна температура (°C)	50
Номинално напрежение	400V
Степен на защита - IP	IP20
Тип продукт	Metered
Number of sockets	30
Outlet type	24 x IEC320 C13 und 6 x IEC320 C19
Номинален ток (A)	32
Phases per feed	3
Начин на свързване	CEE 32 A red
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Монтаж	Bracket (L-shape)

Описание

Артикулен No.

PDU PRO Metered, 24xC13, 6xC19, 400V, 32A, RCM

Measurement per phase, Residual Current Monitoring per phase, incl. mounting bracket with screws, not suitable for 42U enclosures SR3PDIPM11 or smaller!