

Данни за артикула: SR3PDIPM13

PDU PRO Metered, 18xC13, 3xC19, 400V, 16A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU PRO Metered
- Metering per phase
- Input: 16 A / 400 V | 11 kW
- Zuleitung: 3,0 m | 2,5 mm²
- with CEE plug 16 A red
- Output: 18x C13 IEC Socket + 3x C19 IEC Socket
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)
- Packed in cardboard box
- Length 1135 mm

Технически данни

Нето дължина (mm)	1.136,70
Нето широчина (mm)	56,00
Нето височина (mm)	65,00
EAN	4057298208119
ЦЕНА	1.960,00
Мин. околна температура (°C)	0
Макс. околна температура (°C)	50
Номинално напрежение	400V
Степен на защита - IP	IP20
Тип продукт	Metered
Number of sockets	21
Outlet type	18 x IEC320 C13 und 3 x IEC320 C19
Номинален ток (A)	16
Phases per feed	3
Начин на свързване	CEE 16 A red
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Монтаж	Bracket (L-shape)

Описание	Артикулен No.
PDU PRO Metered, 18xC13, 3xC19, 400V, 16A	SR3PDIPM13
Measurement per phase, incl. mounting bracket with screws	