

Данни за артикула: SR3PDIPP04

PDU PRO Metered+, 36xИзхода(C13,C15,C19,C21), 400V, 16A, RCM

Metering per outlet, Residual Current Monitoring per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU PRO Metered+ inkl. RCM
- Metering per socket
- Residual Current Monitoring per phase, Typ B
- Input: 16 A / 400 V | 11 kW
- Supply cable: 3,0 m | 2,5 mm²
- with CEE plug 16 A red
- Output: 36x Combo C13/C15/C19/C21
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display

- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) </l

Технически данни

Нето дължина (mm)	1.696,50
Нето широчина (mm)	56,00
Нето височина (mm)	71,00
EAN	4057298230332
ЦЕНА	4.347,00
Мин. околна температура (°C)	0
Макс. околна температура (°C)	50
Номинално напрежение	400V
Степен на защита - IP	IP20
Тип продукт	Metered+
Number of sockets	36
Outlet type	36 x Combo Socket (C13/C15/C19/C21)
Номинален ток (A)	16
Phases per feed	3
Начин на свързване	CEE 16 A red
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Монтаж	Bracket (L-shape)

Описание	Артикулен No.
PDU PRO Metered+, 36xИзхода(C13,C15,C19,C21), 400V, 16A, RCM Metering per outlet, Residual Current Monitoring per phase, incl. mounting bracket with screws	SR3PDIPP04