

Данни за артикула: SR3PDIPS01

# PDU PRO

## Switched, 24xИзхода(C13, C15, C19, C21), 230V, 16A

Measurement per phase (measurement at socket level can be upgraded with license),  
switchable per socket, includes mounting bracket with screws



### SCHRACK-Info

- PDU PRO Switched
- Metering per phase
- Can be upgraded to measuring per socket at any time via licence (SR3PAB0011,SR3PAB0012,SR3PAB0013)
- switchable sockets
- Input: 16 A / 230 V | 3,6 kW
- Supply cable: 3,0 m | 2,5 mm<sup>2</sup>
- with CEE plug 16 A blue
- Output: 24x Combo C13/C15/C19/C21
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)

- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) &lt;/l

## Технически данни

|                               |                                                                                                                                                        |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Нето дължина (mm)             | 1.191,00                                                                                                                                               |
| Нето ширина (mm)              | 56,00                                                                                                                                                  |
| Нето височина (mm)            | 71,00                                                                                                                                                  |
| EAN                           | 4057298230455                                                                                                                                          |
| ЦЕНА                          | 3.064,00                                                                                                                                               |
| Мин. околна температура (°C)  | 0                                                                                                                                                      |
| Макс. околна температура (°C) | 50                                                                                                                                                     |
| Номинално напрежение          | 230V                                                                                                                                                   |
| Степен на защита - IP         | IP20                                                                                                                                                   |
| Тип продукт                   | Switched                                                                                                                                               |
| Number of sockets             | 24                                                                                                                                                     |
| Outlet type                   | 24 x Combo Socket (C13/C15/C19/C21)                                                                                                                    |
| Номинален ток (A)             | 16                                                                                                                                                     |
| Phases per feed               | 1                                                                                                                                                      |
| Начин на свързване            | CEE 16 A blue                                                                                                                                          |
| Protocol                      | LDAP<br>IPv6<br>IPv4<br>DNS<br>SNMPv1<br>SSH<br>HTTP<br>SNMPv3<br>SNMPv2<br>NTP<br>SSH2<br>DHCP<br>ModBus /TCP<br>SMTP<br>HTTPS<br>SNMP Trap<br>Syslog |
| Монтаж                        | Bracket (L-shape)                                                                                                                                      |

| Описание                                                                                                                                       | Артикулен No. |
|------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| PDU PRO Switched, 24xИзхода(C13, C15, C19, C21), 230V, 16A                                                                                     |               |
| Measurement per phase (measurement at socket level can be upgraded with license), switchable per socket, includes mounting bracket with screws | SR3PDIPS01    |