

Данни за артикула: SR3PDIPS04

PDU PRO Switched, 36xИзхода(C13,C15,C19,C21), 400V, 16A, RCM

Measurement per phase (measurement at socket level can be upgraded with license), Residual Current Monitoring per phase, switchable per socket, includes mounting bracket with screws



SCHRACK-Info

- PDU PRO Switched RCM
- Metering per phase
- Can be upgraded to measuring per socket at any time via licence (SR3PAB0011,SR3PAB0012,SR3PAB0013)
- Residual Current Monitoring per phase, Typ B
- switchable sockets
- Input: 16 A / 400 V | 11 kW
- Supply cable: 3,0 m | 2,5 mm²
- with CEE plug 16 A red
- Output: 36x Combo C13/C15/C19/C21
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors

- 1 x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) </l

Технически данни

Нето дължина (mm)	1.696,50
Нето ширина (mm)	56,00
Нето височина (mm)	71,00
EAN	4057298230530
ЦЕНА	4.514,00
Мин. околна температура (°C)	0
Макс. околна температура (°C)	50
Номинално напрежение	400V
Степен на защита - IP	IP20
Тип продукт	Switched
Number of sockets	36
Outlet type	36 x Combo Socket (C13/C15/C19/C21)
Номинален ток (A)	16
Phases per feed	3
Начин на свързване	CEE 16 A red
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Монтаж	Bracket (L-shape)

Описание	Артикулен No.
PDU PRO Switched, 36xИзхода(C13,C15,C19,C21), 400V, 16A, RCM Measurement per phase (measurement at socket level can be upgraded with license), Residual Current Monitoring per phase, switchable per socket, includes mounting bracket with screws	SR3PDIPS04