

Данни за артикула: WSA1410309

Метално табло за стенен м-ж, с 2 врати IP54, 1400x1000x300mm

RAL7035, с монтажна плоча, 3 точково заключване с въртяща ръкохватка, с 2 фланеца с размер 400x190mm, тип E



SCHRACK-Info

- **Material:** Robust, cross-shaped construction which is welded from a cold-pressed sheet steel plate regardless on the enclosure size. The enclosure consists of two parts: corpus and door
- **Sheet steel thickness corpus:**
 - Single door:
 - 1.2mm: WSA3025150 to WSA8040300
 - 1.5mm: WSA8060210 to WSA1208300
 - Double door:
 - 1.2mm: WSA6080302
 - 1.5mm: WSA8012309 to WSA1410409
- **Gland plates:**
 - Blind gland plates made of 1.5mm powder-coated sheet steel
 - The cable entry is possible via gland plate openings in the bottom or the top because the enclosure can be rotated by 180°
 - The placement far back in the enclosure ensures an easy cable entry
 - A gasket to protect the degree of protection is included
- **Door:** Made of sheet steel and equipped with M6 threaded bolts for earthing
 - Sheet steel thickness:
 - 1.2mm: WSA3025150 to WSA6040300

- 1.5mm: WSA6050210 to WSA8040300, except WSA6080300 + WSA6080302 (each 2mm)
- 2mm: WSA6080300 + WSA6080302, as well as WSA8060210 to WSA1410409
- All single door enclosures from WSA4040210 (H=400 W=400 D=210mm), as well as all double door enclosures are fitted with pre-assembled door-mounting profiles, which also serve for rail fastening
- The door is secured with two and from a height of 1000mm with three hinges and has an opening angle of 130°
- The door hinges are hidden and the door is attached with safety pins. The position of door hinges can be easily changed. The doors have a polyurethane foam seal to ensure the IP degree of protection
- **Lock:**
 - Single door:
 - 1x sash lock with double-bit insert: WSA3025150 to WSA4060210
 - 2x sash locks with double-bit insert: WSA5030210 to WSA1008409
 - 1x 3-point-lock with door lock: WSA1206300 to WSA1208409
 - Double door:
 - 4x sash locks with double-bit insert: WSA6080302 to WSA1010309
 - 1x 3-point-lock with mini-swing handle: WSA1210309 to WSA1410409
 - Single door enclosures from a height of 500mm have two sash locks
 - Single door enclosures from a height of 1200mm are equipped with a 3-point rod lock and a door lock
 - Double door enclosures from a height of 600mm have four sash locks
 - Double door enclosures from a height of 1200mm are equipped with a 3-point rod lock and a mini-swing handle
 - The lock insert for all locking systems is a 5mm double-bit lock
 - The mini-swing handle with 5mm double-bit lock can be exchanged for a door lock or a swing handle for half-cylinder locks
- **Mounting plate:**
 - 2mm galvanised sheet steel
 - The mounting plate is folded on the sides to increase rigidity
 - The mounting plate is installed on welded M8 bolts inside the enclosure and can be removed for assembly and wiring
 - It comes with earthing points to establish a connection to the body of the enclosure
- **Mounting:**
 - The enclosure can be mounted directly to the wall with wall-mounting brackets WSAWB004, the degree of protection is maintained
 - Alternatively, the enclosure can be mounted directly on the desired mounting surface using screws (pay attention to the degree of protection!)
 - The four M8 diameter wall-mounting holes are arranged in the corners of the rear panel
 - Several enclosures can be mounted beside each other thanks to the small door opening radius
 - For the widths 300, 400, 500 and 600mm, there are corresponding pole attachments WSAPCLx00
- **Outdoor installation:**
 - Enclosures and accessories of WSA series meet the requirements of standard IEC 62208 for metal enclosures that allow outdoor installation
 - The standard IEC 62208 allows a certain degree of oxidation Ri1 according to ISO 4628-3 and in practice this degree of oxidation does not affect the functionality and mechanical solidity of the enclosure. The implementation of maintenance to avoid aesthetic deterioration and to prolong its useful life is recommended (see below)
 - Corrosion protection for the entire enclosure is recommended
- **Degree of protection:**
 - Single door IP66
 - Double door IP54
- **Impact protection:** IK10, IK08 for glazed doors
- **Finish:** Iron phosphate and electrostatic powder coating
- **Color:** RAL 7035 (Light grey)

• **Supply includes:**

- Enclosure with two door-mounting profiles (from enclosure width 400mm and above)
- Blind gland plate(s) with gasket(s) and screws
- One key DIN 5mm
- One mounting plate with mounting material
- Earthing possibilities are given

Maintenance recommendations for sheet steel wall-mounted enclosures outdoor:

- Enclosures and accessories of WKT and WSA series meet the requirements of standard **IEC 62208** for metal enclosures that allow outdoor installation
- The standard IEC 62208 allows a certain degree of **oxidation Ri1** according to **ISO 4628-3** and in practice this degree of oxidation does not affect the functionality and mechanical solidity of the enclosure. The implementation of maintenance to avoid aesthetic deterioration and to prolong its useful life is recommended
- **Interval:** Annually
- **Visual inspection:** Detection of any harm to the surface such as scrapes or impacts that could have damaged the paint coating
- **Initial signs of rust:** Due to scrapes, impacts or any other causes
 - Remove the surface rust
 - Abrade the surface rust to get rid of it completely
- **Cleaning:** Clean the affected area with alcohol or an evaporating cleaner
- **Paint:** Paint the affected surface with a synthetic paint (RAL 7035)
 - We recommend our grey textured paint color RAL 7035, Art.-nr. IU008106


Технически данни

Нето широчина (mm)	1.000,00
Нето височина (mm)	1.400,00
Дълбочина (mm)	300,00
Нето тегло (kg)	86,50
Мин. околна температура (°C)	-40
Макс. околна температура (°C)	100
Supply includes	Complete enclosure + mounting plate + gland plates + double bit key + accessory pack
Стандарт на продукта	EN 62208
Степен на защита - IP	IP54
Клас на защита	I
Impact Resistance	IK10
Номинално напрежение	1000V AC / 1500V DC
Цвят	RAL 7035 (Light grey)
Широчина (mm)	1000
Височина (mm)	1400
Дълбочина (mm)	300

Технически данни - продължение

Дебелина на материала на таблото (mm)	1,50
Монтажна плоча	galvanized sheet steel 2mm
Mounting plate wall thickness (mm)	2
Mounting plate width (mm)	950
Mounting plate height (mm)	1375
Дебелина на стената на вратата (mm)	2
Load capacity per door (kg)	30
Брой врати	2
Тип	Wall-mounted Enclosure Sheet Steel
Total Load Capacity (kg)	280
Mounting Plate Load Capacity (kg)	250
Брой гумирани плочи	2
Армиране на врати	Included
Lock	2
Hinge	6
Тип гумирана плоча	E
Широчина на плочата за каб. вх. (mm)	400
Дълбочина на плочата за каб. вх. (mm)	190
Rear wall mounting	4
Разсейвана мощност (W)	-604,00

Dimension Drawing



Таблични файлове: Метално табло за стенен м-ж, с 2 врати IP54, 1400x1000x300mm

Artikel-nummer	Gehäuse (mm)			Wandstärken (mm)		DR	Innere Lichte i.L.	Türen		Flansche				Rückwand	Montageplatte (mm)		
	H	B	T	Korpus	Türe	(mm)	(mm)	Anzahl Schlösser	Anzahl Scharniere	BF (mm)	TF (mm)	Typ	Stk.	Anzahl Befestig.	HM	BM	TM
mit Montageplatte																	
WSA1210302	1200	1000	300	1,5	2	2x 356	283	1 SH*	6	420	100	H	2	4	1175	950	12
WSA1212302	1200	1200	300	1,5	2	2x 456	283	1 SH*	6	520	100	K	2	4	1175	1150	12
WSA1212402	1200	1200	400	1,5	2	2x 456	383	1 SH*	6	520	200	L	2	4	1175	1150	12
WSA1410302	1400	1000	300	1,5	2	2x 356	283	1 SH*	6	420	200	I	2	4	1375	950	12
WSA1410402	1400	1000	400	1,5	2	2x 356	383	1 SH*	6	420	200	I	2	4	1375	950	12

*SH = Mini-Schwenkebel

Таблица с артикули

Описание	Артикулен No.
Метално табло за стенен м-ж, с 2 врати IP54, 1400x1000x300mm RAL7035, с монтажна плоча, 3 точково заключване с въртяща ръкохватка, с 2 фланеца с размер 400x190mm, тип E	WSA1410309
Акcesoари	
LED lighth for EC, infra (not available in this country)	IU006519CZ
Скоби за стенен монтаж за табла WSA, 4 броя galvanized, PU=4 pieces	WSAWB004
Заземителна връзка, дължина 260mm	WSTCUF260
Кабелен вход за WSA, за фланец тип E, с гумирана основа подходящ за WSA5050300, WSA6050300 и WSA6050305	WSAMFROE
Адаптер за гумиран фланец, тип E, за табла WSA с 1 отвор за гумиран фланец, за WSA5050300, WSA6050300 и WSA6050305	WSAVBF06
Гумирана плоча за каб. вх. за WSTVBF, IP55, 17 входа 9x 18-30mm, 4x 10-15mm, 4x 5-10mm, с включени 4 бр. монтажни щипки	WSTBT2117G
Гумирана плоча за каб. вх. за WSTVBF, IP65, 25 входа 1x 20-26mm, 16x 8-14mm, 4x 14-20mm, 4x 5-7mm, с включени 4 бр. монтажни щипки	WSTBT2125G
Гумирана плоча за каб. вх. за WSTVBF, IP65, 6 входа 2x 24-54mm, 1x 30-59mm, 3x 6-14mm, 4x с включени 4 бр. монтажни щипки	WSTBT2130G
Гумирана плоча за каб. вх. за WSTVBF, IP65, 35 входа 1x 17-32mm, 2x 12-18mm, 16x 10-14mm, 12x 7-12mm, 4x 6-10mm, с включени 4 бр. монтажни щипки	WSTBT2135G
Гумирана плоча за каб. вх. за WSTVBF, IP65, 50 входа 49x 7-13mm, 1x 15-25mm, с включени 4 бр. монтажни щипки	WSTBT2150G
Комплект панели за основа, преден и заден, 1000/100mm RAL7012, компл. = 2 бр.	ATSOB101
Странична основа за табла WSA (компл.), 300x100mm RAL7012	WSASOT031
Брава с въртяща ръкохватка за WSA, с полуцилиндър EK 333 подходящ ключ DV905334 (идентичен ключ), подходяща за табла с височина 1200 / 1400mm	WSAS5333
Брава с въртяща ръкохватка за WSA, с "push-button" подходяща за WSA1206300, WSA1206400, WSA1208300, WSA1208400, WSA1210302, WSA1212302, WSA1212402, WSA1410302 и WSA1410402	WSAS3531
Основа / ръкохватка за патрон полуцилиндър 40mm IP65, for half cylinder 40mm	IU001925
Въртяща ръкохватка с капак, за полуцил. 40mm, IP65 Подходяща за табла с височина 1200 / 1400mm	IU001225
Въртяща ръкохватка за полуцилиндър 40mm, IP40 Подходяща за табла с височина 1200 / 1400mm	IU001903

Таблица с артикули

Описание	Артикулен No.
Акcesoари	
Ключалка за табла WSA с 2 врати, 5mm ключ за табла подходящ ключ DV903532	WSAG3532
Монтажен профил за врата, за табла WSA с широчина 1000mm 1 брой	WSACP1000
Изключвател за врата, за WSA над 400x400mm, 6A, 230V, IP40 1x normally open (NO) and 1x normally closed contact (NC), plastic, suitable for WSA enclosures beginning from HxW 400x400mm	WSADSW01
Ограничител за врата за табла WSA, подходящ за всички разм.	WSADSTP2
Козирка за защита от вода, за табла WSA, 1000x300mm подходяща за WSA1010302, WSA1210302 и WSA1410302	WSAD1030