

Данни за артикула: WST4030210

Табло метално за стенин м-ж, с 1 врата, IP65, 400x300x210mm

Метални, RAL7035, с монтажна плоча, с 1 двойна ключалка, с 1 плоча за кабелни
входове Ш=192 Д=62 mm



SCHRACK-Info

- Material: Solid, cross-shaped construction, which is folded and welded from a cold-pressed sheet steel plate regardless of the size of the enclosure.
- The enclosure consists of two parts: Body and door.
- Gland plates: 1.4mm powder coated sheet steel. The body front of the enclosure is a double-edged rain gutter to allow water to drain. The enclosure can be rotated by 180°, so the cable entry is possible via gland plate openings in the base or at the top. 4 wall mounting holes with 8.5mm diameter arranged in the corners of the rear wall. All mounting holes have 20mm edge distance. All parts are pre-treated with iron phosphate, demineralised and protected by an epoxy-polyester powder-structure coating in RAL7035.
- The door is secured by hinges and has an opening angle of 130°. The door is mounted using safety pins and the hinges are hidden. The door hinge can be changed easily from right to left. The doors have a foamed polyurethane seal.
- Mounting plate: Galvanised sheet steel, 2mm, folded on all sides. The mounting plate folded on all sides is mounted on welded M8 bolts on the rear of the enclosure and can be removed for mounting and wiring. The mounting plate is made of 2mm sendzimir galvanized sheet steel to comply with EMC guidelines. It has earthing points to establish a connection to the enclosure body.
- Protection class: Maximum protection for the devices is guaranteed due to the high degree of protection and impact resistance IK10 according to IEC 60529 standards. Corrosion protection for additional drilling should be considered.

- Mounting: The enclosure is mounted to the wall with screws (with plastic washers inside) directly with the rear wall or with a mounting kit (accessory WSTWB004 / WSTWB006), in both cases the IP degree of protection is maintained. The small opening radius of the doors makes it easy to mount enclosures directly next to each other.
- Delivery includes: Complete enclosure with gasket and screws, keys DIN 5mm and mounting plate incl. mounting material. Grounding possibilities are given.



Технически данни

Нето широчина (mm)	300,00
Нето височина (mm)	400,00
Дълбочина (mm)	210,00
Нето тегло (kg)	7,67
Мин. околна температура (°C)	-20
Макс. околна температура (°C)	70
Дебелина на стената на вратата (mm)	1,20
Mounting plate height (mm)	340
Цвят	RAL 7035 (Light grey)
Load capacity per door (kg)	20
Брой врати	1
Височина (mm)	400
Дълбочина (mm)	210
Степен на защита - IP	IP65
Mounting plate wall thickness (mm)	2
Клас на защита	I
Дебелина на материала на таблото (mm)	1,20
Монтажна плоча	galvanized sheet steel 2mm
Mounting plate width (mm)	250
Широчина (mm)	300
Акcesoари	WSTWB004--; WSTCUF260-; WSTCEG2806; WSTCEG4010; WSTCEG5008; WSTCEG5007; WSTL3532--; WSSL3844-A; DV905333--
Тип	Wall-mounted enclosure sheet steel
Total Load Capacity (kg)	80
Mounting Plate Load Capacity (kg)	55
Брой гумирани плочи	1
Армиране на врати	Included
Lock	1
Hinge	2
Тип гумирана плоча	A
Широчина на плочата за каб. вх. (mm)	192
Дълбочина на плочата за каб. вх. (mm)	62
Rear wall mounting	4
Разсейвана мощност (W)	-78,00

Dimension drawing




Таблица с артикули

Описание	Артикулен No.
Табло метално за стенен м-ж, с 1 врата, IP65, 400x300x210mm	WST4030210
Метални, RAL7035, с монтажна плоча, с 1 двойна ключалка, с 1 плоча за кабелни входи Ш=192 Д=62 mm	
Акcesoари	
Скоби за стенен монтаж за табла WST, с вис. до 800mm	WSTWB004
Комплект 4 бр.	
Заземителна връзка, дължина 260mm	WSTCUF260
Гумиран кабелен вход 28mm, 6 входа, (10 броя)	WSTCEG2806
3x 3,4mm, 3x 5-9mm	
Гумиран кабелен вход 40mm, 10 входа, (10 броя)	WSTCEG4010
3x 5-14mm, 7x 2-7mm	
Гумиран кабелен вход 50mm, 8 входа, (5 броя)	WSTCEG5008
2x 3-7mm, 1x 12-21mm, 1x 7-15mm, 4x 4-10mm	
Гумиран кабелен вход 50mm, 7 входа, (5 броя)	WSTCEG5007
7x 6-13mm	
Стандартна ключалка 5 mm за табла WST	WSTL3532
подходящ ключ = DV903532	
Секретна ключалка за табла WSA, с 1 ключ EK 333	WSSL3844-A
Секретна ключалка за табла WST, с ключ 5333	DV905333
с два ключа тип 5333	